



US009409201B2

(12) **United States Patent**
Summons et al.

(10) **Patent No.:** **US 9,409,201 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **SYSTEM AND METHOD OF PROVIDING INDIVIDUAL QUANTITIES OF CUSTOM COLORED SEALING COMPOUND**

USPC 222/129, 142, 142.1, 327, 543, 325, 222/326, 386, 391; 220/629; 206/219, 221; 141/114

See application file for complete search history.

(71) Applicant: **Sashco, Inc.**, Brighton, CO (US)

(72) Inventors: **Wayne Summons**, Thornton, CO (US);
Elliot Summons, Centennial, CO (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **SASHCO, INC.**, Brighton, CO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

3,417,910	A *	12/1968	Johnson	229/117.25
3,735,900	A *	5/1973	Gores	222/129
4,350,774	A *	9/1982	Scotti et al.	C08J 9/14 222/394
4,826,047	A *	5/1989	Heflin	222/136
4,953,729	A *	9/1990	Kloosterhouse	215/255
5,129,520	A *	7/1992	Gaspar	206/534
5,277,303	A *	1/1994	Goyet et al.	206/221
5,297,697	A *	3/1994	Boring	222/83

(Continued)

(21) Appl. No.: **14/318,888**

(22) Filed: **Jun. 30, 2014**

(65) **Prior Publication Data**

US 2014/0319166 A1 Oct. 30, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/037,011, filed on Feb. 28, 2011, now Pat. No. 8,800,816, which is a continuation-in-part of application No. 12/410,301, filed on Mar. 24, 2009, now Pat. No. 8,100,296, which is a continuation of application No. 12/053,865, filed on Mar. 24, 2008.

Primary Examiner — Patrick M Buechner

Assistant Examiner — Jeremy W Carroll

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP

(51) **Int. Cl.**

B67D 7/74 (2010.01)
B05C 17/005 (2006.01)
B05C 17/00 (2006.01)

(57) **ABSTRACT**

A system and method for providing custom colored sealant are generally provided with a dispensing container, containing a quantity of sealant base solution. A bottom wall of the dispensing container is positioned to limit any headspace within the interior of the dispensing container until the contents are ready to be mixed. The bottom wall is moved prior to adding a coloring agent to the dispensing container, which is mixed with the sealant base by agitating the dispensing container, until a desired color is attained. A sealant thickener may then be added and mixed by similar agitation of the dispensing container. A rod may be provided to engage and move the bottom wall. A pull string may also be provided to move the bottom wall. A nozzle is then coupled with the dispensing container and the custom-colored sealant is ready to be dispensed.

(52) **U.S. Cl.**

CPC **B05C 17/00593** (2013.01); **B05C 17/003** (2013.01); **B05C 17/0052** (2013.01); **B05C 17/00553** (2013.01); **B05C 17/00556** (2013.01); **B05C 17/00563** (2013.01); **B05C 17/00583** (2013.01); **B05C 17/00513** (2013.01)

(58) **Field of Classification Search**

CPC B05C 17/003; B05C 17/00553; B05C 17/00556; B05C 17/00583; B05C 17/00563; B05C 17/00593; B05C 17/0052; B05C 17/00513

14 Claims, 23 Drawing Sheets

