

[54] **COATING WITH IMPROVED ADHESION**

[75] **Inventor:** **Anthony J. Dinallo, Sr.,**
Mechanicville, N.Y.

[73] **Assignee:** **General Electric Company,**
Waterford, N.Y.

[21] **Appl. No.:** **332,820**

[22] **Filed:** **Apr. 3, 1989**

[51] **Int. Cl.⁵** **C08K 5/24**

[52] **U.S. Cl.** **524/265; 524/266;**
524/267; 524/268; 524/731

[58] **Field of Search** **524/265, 266, 267, 268,**
524/731

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,340,710 7/1982 Brown, Jr. 525/478

Primary Examiner—Melvyn I. Marquis

[57] **ABSTRACT**

A latent curable electronic coating composition is described which comprises:

- a. a linear dimethylvinyl chainstopped polydimethylsiloxane fluid having a viscosity of about 500 to 5000 centipoise at 25° C.;
- b. an organohydrogenpolysiloxane;
- c. an amount of a platinum catalyst sufficient to cause the co-reaction of (a) and (b);
- d. a combination of inhibiting agents comprised of (i) an ethylenically unsaturated isocyanurate and (ii) a dialkyl acetylenedicarboxylate; and
- e. a silanol-containing dimethyl siloxane hydrolyzate having a silanol content from about 0.5% to about 1.5% and a viscosity from about 4 to about 40 centipoise at 25° C.

9 Claims, No Drawings