US007289102B2

(12) **United States Patent**
Hinckley et al.

(10) **Patent No.: US 7,289,102 B2**
(45) **Date of Patent: Oct. 30, 2007**

(54) **METHOD AND APPARATUS USING MULTIPLE SENSORS IN A DEVICE WITH A DISPLAY**

(75) Inventors: **Kenneth P. Hinckley**, Redmond, WA (US); **Michael J. Sinclair**, Kirkland, WA (US); **Jeffrey Scott Pierce**, Pittsburgh, PA (US); **Eric J. Horvitz**, Kirkland, WA (US)

(73) Assignee: **Microsoft Corporation**, Redmond, WA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 182 days.

(21) Appl. No.: **09/875,477**

(22) Filed: **Jun. 6, 2001**

(65) **Prior Publication Data**

US 2002/0021278 A1 Feb. 21, 2002

Related U.S. Application Data

(60) Provisional application No. 60/218,748, filed on Jul. 17, 2000.

(51) **Int. Cl.**
G09G 5/00 (2006.01)

(52) **U.S. Cl.** **345/156**; 345/157; 345/158; 345/160; 345/161; 345/163; 345/173

(58) **Field of Classification Search** 345/156–172
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,504,701 A		3/1985	Lucchesi	379/373.02
5,329,577 A		7/1994	Norimatsu	455/567
5,337,353 A		8/1994	Boi et al.	379/433.01
5,481,595 A		1/1996	Ohashi et al.	379/67
5,602,566 A	*	2/1997	Motosyuku et al.	345/684
5,657,372 A		8/1997	Ahlberg et al.	455/414
5,661,632 A	*	8/1997	Register	361/683
5,689,665 A		11/1997	Mitsui et al.	395/342
5,705,997 A	*	1/1998	Park	340/825.49
5,712,911 A		1/1998	Her	379/388.01
5,714,997 A	*	2/1998	Anderson	348/39
5,761,071 A	*	6/1998	Bernstein et al.	700/237
5,860,016 A	*	1/1999	Nookala et al.	713/324

(Continued)

FOREIGN PATENT DOCUMENTS

JP 8-292826 * 11/1996

(Continued)

OTHER PUBLICATIONS

Bartlett, J.F., "Rock'n'Scroll Is Here to Stay," IEEE Computer Graphics and Applications, pp. 40-45, (May/Jun. 2000).

(Continued)

Primary Examiner—Richard Hjerpe
Assistant Examiner—Leonid Shapiro
(74) *Attorney, Agent, or Firm*—Theodore M. Magee; Westman, Champlin & Kelly, P.A.

(57) **ABSTRACT**

In a device having a display, at least one sensor signal is generated from a sensor in the device. One or more context values are then generated from the sensor signal. The context values indicate how the device is situated relative to one or more objects. At least one of the context values is then used to control the operation of one or more aspects of the device.

25 Claims, 6 Drawing Sheets