

(12) **United States Patent**
Wheeler et al.

(10) **Patent No.:** **US 9,410,303 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **APPARATUS FOR DRILLING SITE CONTAINMENT**

(71) Applicants: **Matthew Wheeler**, Longview, TX (US);
Lee Honeycutt, Longview, TX (US);
Chris Allen, Columbia Crossroads, PA (US)

(72) Inventors: **Matthew Wheeler**, Longview, TX (US);
Lee Honeycutt, Longview, TX (US);
Chris Allen, Columbia Crossroads, PA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/664,403**

(22) Filed: **Mar. 20, 2015**

(65) **Prior Publication Data**
US 2015/0191889 A1 Jul. 9, 2015

Related U.S. Application Data

(63) Continuation of application No. 13/688,517, filed on Nov. 29, 2012, now Pat. No. 9,016,980.

(51) **Int. Cl.**
B65D 90/24 (2006.01)
E21B 41/00 (2006.01)
E02D 31/00 (2006.01)
B09C 1/00 (2006.01)
B08B 17/02 (2006.01)
B65G 3/04 (2006.01)
E04H 7/02 (2006.01)

(52) **U.S. Cl.**
CPC **E02D 31/004** (2013.01); **B08B 17/025** (2013.01); **B09C 1/00** (2013.01); **B65D 90/24** (2013.01); **B65G 3/04** (2013.01); **E04H 7/02** (2013.01); **E21B 41/00** (2013.01)

(58) **Field of Classification Search**

CPC B65D 90/24; E02D 31/004; B09C 1/00; E21B 41/00

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,454,195 A *	10/1995	Hallsten	B65D 90/24 220/495.01
5,689,920 A *	11/1997	Hallsten	B65D 90/24 220/495.01
6,258,430 B1 *	7/2001	Perlman	E04H 6/428 180/69.1
6,695,534 B2 *	2/2004	Cain	B65D 90/24 405/114
9,016,980 B2 *	4/2015	Wheeler	B09C 1/00 405/129.45
2004/0096276 A1 *	5/2004	Startteim	E02D 27/01 405/129.8
2012/0076588 A1 *	3/2012	Dupuis	F01M 11/03 405/107
2013/0105475 A1 *	5/2013	Marshall	B65D 90/24 220/4.12
2013/0121768 A1 *	5/2013	Powell	E02D 31/00 405/114

* cited by examiner

Primary Examiner — Frederick L Lagman

(74) *Attorney, Agent, or Firm* — Conley Rose, P.C.; Grant Rodolph

(57) **ABSTRACT**

An apparatus for protecting against environmental contamination at a drilling site is disclosed. The apparatus is used to form a perimeter around the drilling site, the interior of which is covered by a geomembrane. The portion of the geomembrane found along the perimeter is placed in the groove of the apparatus's base. A key block is then fit into the groove, thereby holding the geomembrane in place by the tension created between the base and the key block. At those perimeter locations that will be traversed by vehicles and equipment, two ramp pieces replace the key block in holding the geomembrane tight against the base.

18 Claims, 5 Drawing Sheets

