US006515704B1

(12) **United States Patent**
Sato

(10) **Patent No.: US 6,515,704 B1**
(45) **Date of Patent: Feb. 4, 2003**

(54) **APPARATUS AND METHOD FOR SENSING AND DISPLAYING AN IMAGE**

(75) Inventor: **Kazuya Sato**, Kawasaki (JP)

(73) Assignee: **Canon Kabushiki Kaisha**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/028,227**

(22) Filed: **Feb. 23, 1998**

(30) **Foreign Application Priority Data**

Feb. 24, 1997 (JP) 9-054311

(51) **Int. Cl.**[7] **H04N 5/225**
(52) **U.S. Cl.** **348/333.11**; 348/333.05
(58) **Field of Search** 348/207, 211, 348/212, 213, 222, 231, 232, 333.01, 333.02, 333.05, 333.11, 333.12, 143, 14.08, 14.09, 14.1; 345/638; H04N 5/225

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,903,309 A * 5/1999 Anderson 348/333
5,943,050 A * 8/1999 Bullock et al. 345/340
5,999,214 A * 12/1999 Inagaki 348/211
6,147,703 A * 11/2000 Miller et al. 348/220

* cited by examiner

Primary Examiner—Tuan Ho
(74) *Attorney, Agent, or Firm*—Morgan & Finnegan, LLP

(57) **ABSTRACT**

According to an image sensing apparatus and an image display method therefor of this embodiment, since a preview image to be photographed and a viewing thumbnail image can be simultaneously displayed on one screen, and the display form can be arbitrarily changed by a simple selection operation on the screen, the visibility and operability of the image sensing apparatus can be largely improved.

31 Claims, 11 Drawing Sheets