

15

applying the electrical energy to a load;
 providing a plurality of different values for a threshold at
 a plurality of moments in time and corresponding to an
 electrical characteristic of the electrical energy;
 adjusting an amount of the electrical energy applied to the
 load responsive to an electrical characteristic of the
 electrical energy triggering one of the values of the
 threshold at the respective moment in time; and
 monitoring frequency of the electrical energy, and
 wherein the adjusting is responsive to the monitoring.

2. The method of claim 1 wherein the adjusting comprises
 adjusting responsive to the frequency of the electrical energy
 dropping below the one of the values of the threshold.

3. The method of claim 1 wherein the applying comprises
 applying the electrical energy to the load located at a
 customer location, and the monitoring comprises monitoring
 using control circuitry located proximate to the customer
 location.

4. The method of claim 1 wherein the applying comprises
 applying the electrical energy to the load located at a
 customer location, and the adjusting comprises adjusting
 using control circuitry located proximate to the customer
 location.

5. The method of claim 4 wherein the control circuitry
 comprises control circuitry of a power management device
 coupled with the load.

6. The method of claim 4 wherein the control circuitry
 comprises control circuitry of the load.

7. The method of claim 1 wherein the providing the
 different values comprises randomly assigning the values.

8. The method of claim 1 wherein the providing com-
 prises providing the different values according to a statistical
 distribution.

9. The method of claim 1 wherein the adjusting comprises
 reducing the amount of the electrical energy, and further
 comprising:

monitoring a length of time of the adjustment; and
 increasing an amount of the electrical energy applied to
 the load responsive to the length of time exceeding a
 time out.

10. The method of claim 1 wherein the adjusting com-
 prises adjusting for a variable length of time.

11. The method of claim 1 wherein the adjusting com-
 prises adjusting for a random length of time.

12. The method of claim 1 wherein the adjusting com-
 prises reducing the amount of electrical energy applied to the
 load.

13. The method of claim 1 wherein the adjusting com-
 prises ceasing the applying of the electrical energy.

14. An electrical power distribution control method com-
 prising:

providing electrical energy from an electrical power dis-
 tribution system;
 applying the electrical energy to a load;
 randomly selecting a value of a threshold corresponding
 to an electrical characteristic of the electrical energy of
 the electrical power distribution system; and
 adjusting an amount of the electrical energy applied to the
 load responsive to the electrical characteristic of the
 electrical energy triggering the value of the threshold.

15. The method of claim 14 wherein the randomly select-
 ing comprises randomly selecting a plurality of different
 values of the threshold at a plurality of moments in time.

16. The method of claim 14 wherein the adjusting com-
 prises adjusting using control circuitry, and further compris-
 ing applying operational power to the control circuitry, and

16

wherein the randomly selecting comprises randomly select-
 ing responsive to the applying of the operational power to the
 control circuitry.

17. The method of claim 14 further comprising monitor-
 ing the electrical characteristic of the electrical energy with
 respect to the value of the threshold, and wherein the
 adjusting is responsive to the monitoring.

18. The method of claim 14 wherein the randomly select-
 ing comprises randomly selecting according to a statistical
 distribution.

19. The method of claim 14 wherein the monitoring
 comprises monitoring frequency of the electrical energy.

20. The method of claim 14 wherein the adjusting com-
 prises adjusting for a variable length of time.

21. The method of claim 14 wherein the adjusting com-
 prises adjusting for a random length of time.

22. The method of claim 14 wherein the randomly select-
 ing comprises randomly selecting responsive to electrical
 noise.

23. An electrical power distribution control method com-
 prising:

receiving electrical energy from an electrical power dis-
 tribution system using control circuitry of a power
 management device;

applying electrical energy of the electrical power distri-
 bution system to a load using the control circuitry;

monitoring an electrical characteristic of the received
 electrical energy using the control circuitry;

adjusting the applying at a plurality of moments in time
 responsive to the monitoring, wherein the adjusting
 comprises adjusting an amount of the electrical energy
 applied to the load for a plurality of different lengths of
 time at the respective moments in time; and

randomly selecting the different lengths of time respon-
 sive to initialization of circuitry of the power manage-
 ment device.

24. The method of claim 23 wherein the monitoring
 comprises monitoring frequency of the electrical energy.

25. The method of claim 23 wherein the load comprises
 the control circuitry.

26. The method of claim 23 wherein the randomly select-
 ing comprises initializing the circuitry at the respective
 moments in time.

27. The method of claim 23 wherein the initialized
 circuitry comprises memory circuitry.

28. The method of claim 27 wherein the memory circuitry
 provides a plurality of random numbers during initialization
 at the respective moments in time, and the randomly select-
 ing comprises randomly selecting the different lengths of
 time using respective ones of the random numbers.

29. The method of claim 27 wherein the memory circuitry
 provides the random numbers resulting from electrical noise
 at the respective moments in time.

30. The method of claim 27 wherein the memory circuitry
 comprises memory circuitry of the control circuitry.

31. The method of claim 27 further comprising applying
 power to the memory circuitry to provide the initialization.

32. The method of claim 31 wherein the initialization
 comprises re-initializing the memory circuitry after the
 applying of the power.

33. An electrical power distribution control method com-
 prising:

providing electrical energy using a grid of an electrical
 power distribution system;

applying the electrical energy to a plurality of loads
 coupled with the electrical power distribution system;