



US009409708B1

(12) **United States Patent**
Watts

(10) **Patent No.:** **US 9,409,708 B1**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **DUMPSTER LID OPENING SYSTEM**

(71) Applicant: **Gerald W. Watts**, Clearwater, FL (US)

(72) Inventor: **Gerald W. Watts**, Clearwater, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 44 days.

(21) Appl. No.: **14/335,279**

(22) Filed: **Jul. 18, 2014**

Related U.S. Application Data

(63) Continuation-in-part of application No. 13/894,336, filed on May 14, 2013, now abandoned, which is a continuation-in-part of application No. 13/454,214, filed on Apr. 24, 2012, now abandoned, which is a continuation-in-part of application No. 12/803,795, filed on Jul. 8, 2010, now Pat. No. 8,439,218.

(51) **Int. Cl.**

B65D 43/26 (2006.01)
B65F 1/14 (2006.01)
B65F 1/16 (2006.01)

(52) **U.S. Cl.**

CPC **B65F 1/163** (2013.01); **B65F 2001/1653** (2013.01)

(58) **Field of Classification Search**

CPC B56F 1/163
USPC 220/262, 263, 264
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

963,079 A * 7/1910 Sebring B65D 85/12
217/57
1,131,774 A * 3/1915 Davis B65F 1/163
220/263

1,507,040 A * 9/1924 Zifferer B65F 1/163
220/263
2,046,777 A * 7/1936 Geibel B65F 1/08
220/23.87
2,120,520 A * 6/1938 Kamenstein B65F 1/163
220/263
2,127,594 A * 8/1938 Grossman A47B 77/14
206/223
2,419,163 A * 4/1947 Pope, Sr. B65F 1/08
182/129
2,456,840 A * 12/1948 Rogers B65F 1/163
220/263
2,736,454 A * 2/1956 McConnell D06F 95/002
220/23.2
2,888,162 A * 5/1959 Herpich B65F 1/1623
220/830
3,450,297 A * 6/1969 Clerk B65F 1/163
220/263
4,526,288 A * 7/1985 Schuld B65D 43/262
220/263
4,625,888 A * 12/1986 Thompson B65D 90/623
220/262
5,011,036 A * 4/1991 Souza B65F 1/163
220/263
5,158,198 A * 10/1992 Melideo B65D 88/126
220/263

(Continued)

Primary Examiner — Fenn Mathew
Assistant Examiner — Chetan Chandra

(57) **ABSTRACT**

A container has a base plate and front and rear and side walls. A lid with a hinge is located above the front and rear and side walls. A pivot bar is attached to the lid. The pivot bar has a long extent and a short extent attached to the lid. An actuation assembly is coupled to the container and includes a lower component and a pedal secured to the lower component. The pedal is adapted to be depressed to move the lower component. An upper component is secured to the lower component for reciprocating movement in a plane parallel with the rear wall. A line has a lower end coupled to the upper component and an upper end coupled to the pivot bar.

3 Claims, 10 Drawing Sheets

