



US009409509B2

(12) **United States Patent**  
**Bohlke et al.**

(10) **Patent No.:** **US 9,409,509 B2**

(45) **Date of Patent:** **Aug. 9, 2016**

(54) **DEVICE FOR SECURING STORED MATERIALS IN A STORAGE SPACE AND SECURING ELEMENT THEREFOR**

(58) **Field of Classification Search**  
CPC ..... F16B 2/04; B60P 7/0815; B60P 7/08; B60R 5/04; Y10T 24/44026  
USPC ..... 248/222.13; 410/104, 101, 105  
See application file for complete search history.

(71) Applicants: **Hartmut Bohlke**, Wuppertal (DE);  
**Juergen Salewski**, Duesseldorf (DE);  
**Wolfgang Sitzler**, Wuppertal (DE);  
**Wolfram Zummack**, Troisdorf (DE);  
**Bogdan Tutelea**, Leichlingen (DE);  
**Andreas Goebbels**, Kuerten (DE)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,585,465 B1 \* 7/2003 Hammond ..... B60P 7/0815  
410/104  
6,592,310 B2 \* 7/2003 Hyp ..... B60P 7/0807  
296/65.13

(Continued)

FOREIGN PATENT DOCUMENTS

DE 10 2005 061 493 A1 7/2007  
DE 10 2011 087 363 A1 5/2013  
DE 10 2012 221 386 A1 5/2014

OTHER PUBLICATIONS

Examination Report of German Patent Office issued in Application No. 10 2013 222 651.9 dated Aug. 6, 2014 (5 pages).

*Primary Examiner* — Anita M King

(74) *Attorney, Agent, or Firm* — Flynn, Thiel, Boutell & Tanis, P.C.

(72) Inventors: **Hartmut Bohlke**, Wuppertal (DE);  
**Juergen Salewski**, Duesseldorf (DE);  
**Wolfgang Sitzler**, Wuppertal (DE);  
**Wolfram Zummack**, Troisdorf (DE);  
**Bogdan Tutelea**, Leichlingen (DE);  
**Andreas Goebbels**, Kuerten (DE)

(73) Assignee: **BOS GMBH & CO. KG**, Ostfildern (DE)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 21 days.

(21) Appl. No.: **14/534,520**

(22) Filed: **Nov. 6, 2014**

(65) **Prior Publication Data**

US 2015/0121666 A1 May 7, 2015

(30) **Foreign Application Priority Data**

Nov. 7, 2013 (DE) ..... 10 2013 222 651

(51) **Int. Cl.**  
**B61D 45/00** (2006.01)  
**B60P 7/08** (2006.01)  
**F16B 2/04** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **B60P 7/0815** (2013.01); **F16B 2/04** (2013.01); **Y10T 24/44026** (2015.01)

(57) **ABSTRACT**

A device having a securing element which can be blocked in a load rail which is anchored so as to be fixed to a vehicle, the securing element having a base member with a retention region which can be inserted into the load rail in a positive-locking manner, and the base member includes at least one bar member for engagement in a catch bar arrangement of the load rail which is supported so as to be able to be moved relative to the base member. A additional bar is provided which is movably supported parallel with the bar member and independently of the bar member, and which is resiliently loaded in the direction of the blocking position and which can be moved together with the bar member into the release position.

**8 Claims, 4 Drawing Sheets**

