

(12) **United States Patent**  
**Suzuki et al.**

(10) **Patent No.:** **US 9,410,710 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **PURIFIED AIR DISCHARGE DEVICE**

(75) Inventors: **Taketo Suzuki**, Tokyo (JP); **Tomoyuki Kakinuma**, Tokyo (JP); **Kozo Nitta**, Tokyo (JP); **Yuki Fujishiro**, Tokyo (JP); **Kazuma Fukiura**, Tokyo (JP); **Takahiro Sato**, Tokyo (JP)

(73) Assignee: **Koken Ltd.**, Tokyo (JP)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 232 days.

(21) Appl. No.: **14/347,330**

(22) PCT Filed: **Jun. 22, 2012**

(86) PCT No.: **PCT/JP2012/066033**  
§ 371 (c)(1),  
(2), (4) Date: **Aug. 18, 2014**

(87) PCT Pub. No.: **WO2013/051311**  
PCT Pub. Date: **Apr. 11, 2013**

(65) **Prior Publication Data**  
US 2015/0128541 A1 May 14, 2015

(30) **Foreign Application Priority Data**  
Oct. 3, 2011 (JP) ..... 2011-219659  
May 22, 2012 (JP) ..... 2012-116855

(51) **Int. Cl.**  
**F24F 3/16** (2006.01)  
**F24F 9/00** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **F24F 3/1607** (2013.01); **F24F 3/1603** (2013.01); **F24F 9/00** (2013.01);  
(Continued)

(58) **Field of Classification Search**

CPC ..... B01D 46/00; B01D 46/0013; B01D 46/0023; B23K 9/321; F24F 3/1607; F24F 3/161; F24F 13/068; F24F 7/06  
USPC ..... 55/385.2, DIG. 18, DIG. 29, DIG. 46; 454/49, 56, 59, 184, 187, 188, 189  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,998,142 A 12/1976 Foreman et al.  
4,023,472 A 5/1977 Grunder et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

JP 55-118754 9/1980  
JP 57-28225 2/1982

(Continued)

**OTHER PUBLICATIONS**

EESR for App. No. 12820022.7 (counterpart of U.S. Appl. No. 14/234,737) issued on Feb. 23, 2015.

(Continued)

*Primary Examiner* — Duane Smith

*Assistant Examiner* — Minh-Chau Pham

(74) *Attorney, Agent, or Firm* — Greer Burns & Crain Ltd.

(57) **ABSTRACT**

A purified air discharge device includes a push hood (2) having an air flow discharge surface (23) discharging a uniform purified air flow. The push hood (2) is provided with a lateral air discharger (28) for creating a purified air flow that collides against a surrounding wall that is formed as the push hood (2) is installed and that is installed close along the circumferential direction of the air flow discharge surface (23) of the push hood (2).

**10 Claims, 5 Drawing Sheets**

