



(12) **United States Patent**  
**Vanderelli et al.**

(10) **Patent No.:** **US 7,027,311 B2**  
(45) **Date of Patent:** **Apr. 11, 2006**

(54) **METHOD AND APPARATUS FOR A WIRELESS POWER SUPPLY**

(56) **References Cited**

(75) Inventors: **Timm A. Vanderelli**, Ligonier, PA (US); **John G. Shearer**, Ligonier, PA (US); **John R. Shearer**, Pittsburgh, PA (US)

(73) Assignee: **FireFly Power Technologies, Inc.**, Ligonier, PA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/966,880**

(22) Filed: **Oct. 15, 2004**

(65) **Prior Publication Data**

US 2005/0104453 A1 May 19, 2005

**Related U.S. Application Data**

(60) Provisional application No. 60/511,860, filed on Oct. 17, 2003.

(51) **Int. Cl.**  
**H02M 5/00** (2006.01)

(52) **U.S. Cl.** ..... **363/8**

(58) **Field of Classification Search** ..... 363/8, 363/59, 60, 157, 164, 165

See application file for complete search history.

U.S. PATENT DOCUMENTS

4,703,190 A *	10/1987	Tamura et al. ....	307/2
5,612,652 A *	3/1997	Crosby .....	333/24 R
5,737,177 A *	4/1998	Mett et al. ....	361/234
5,898,911 A *	4/1999	White .....	455/232.1
6,094,161 A *	7/2000	Cassen et al. ....	342/175
6,633,750 B1 *	10/2003	Dacus et al. ....	455/126
6,841,981 B1 *	1/2005	Smith et al. ....	323/312

\* cited by examiner

*Primary Examiner*—Matthew V. Nguyen

(74) *Attorney, Agent, or Firm*—Ansel M. Schwartz

(57) **ABSTRACT**

An apparatus for a wireless power supply including a mechanism for receiving a range of RF radiation across a collection of frequencies. The apparatus includes a mechanism for converting the RF radiation across the collection of frequencies, preferably at a same time into DC. A method for a wireless power supply including the steps of receiving a range of RF radiation across a collection of frequencies. There is the step of converting the RF radiation across the collection of frequencies, preferably at a same time into DC.

**20 Claims, 2 Drawing Sheets**

