



US009409212B2

(12) **United States Patent**
Käske

(10) **Patent No.:** **US 9,409,212 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **NOZZLE APPARATUS AND CLEANING APPARATUS HAVING SUCH NOZZLE APPARATUS**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Dürr Ecoclean GmbH**, Filderstadt (DE)

4,515,313 A 5/1985 Cavanagh
5,000,795 A 3/1991 Chung et al.
5,540,247 A 7/1996 Kawatani et al.
6,199,568 B1 3/2001 Arai et al.

(72) Inventor: **Egon Käske**, Aachen (DE)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Dürr Ecoclean GmbH**, Filderstadt (DE)

DE 2409 544 9/1974
DE 28 55 906 7/1980

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 465 days.

(Continued)

OTHER PUBLICATIONS

(21) Appl. No.: **13/965,744**

International Searching Authority, "International Preliminary Report on Patentability", issued in connection with International Patent Application No. PCT/EP2012/050631, mailed Aug. 29, 2013, 10 pages.

(22) Filed: **Aug. 13, 2013**

German Patent Office, "Search Report," issued in corresponding German Application No. 10 2011 004 232.6 on Nov. 28, 2011, 12 pages.

(65) **Prior Publication Data**

US 2013/0333732 A1 Dec. 19, 2013

(Continued)

Related U.S. Application Data

(63) Continuation-in-part of application No. PCT/EP2012/050631, filed on Jan. 17, 2012.

Primary Examiner — Eric Golightly

(74) *Attorney, Agent, or Firm* — Hanley, Flight and Zimmerman, LLC

(30) **Foreign Application Priority Data**

Feb. 16, 2011 (DE) 10 2011 004 232

(57) **ABSTRACT**

A nozzle apparatus for the generation of at least one fluid stream, the nozzle apparatus comprising: a body having a nozzle chamber comprising a nozzle opening for generating a fluid stream, wherein the body is rotatably mounted on a unit and is movable about a rotation axis, wherein the nozzle opening comprises a wall and a slit-shaped nozzle mouth extending along a slit axis, and wherein the nozzle chamber opens into an opening slot formed in the wall of the body between the nozzle mouth and the nozzle chamber, fluid being fed to the opening slot through an opening in a hollow body via a stream path directed by wall sections of the nozzle chamber to the opening slot, wherein the wall sections are located opposite the opening.

(51) **Int. Cl.**

B08B 3/00 (2006.01)
B08B 3/10 (2006.01)
B05B 1/04 (2006.01)
B08B 3/02 (2006.01)

(52) **U.S. Cl.**

CPC **B08B 3/102** (2013.01); **B05B 1/044** (2013.01); **B08B 3/02** (2013.01)

(58) **Field of Classification Search**

None
See application file for complete search history.

18 Claims, 8 Drawing Sheets

