

[54] METHOD AND APPARATUS FOR PACKETING OBJECTS IN A CHAIN OF BAGS

[75] Inventor: Ralph Widenbäck, Stenungsund, Sweden

[73] Assignee: New Pac Systems AB, Sweden

[21] Appl. No.: 275,066

[22] Filed: Nov. 21, 1988

[30] Foreign Application Priority Data

Nov. 24, 1987 [SE] Sweden 8704666

[51] Int. Cl.⁵ B65B 5/02; B65B 7/06; B65B 9/08; B65B 43/26

[52] U.S. Cl. 53/459; 53/385; 53/469; 53/570; 493/198

[58] Field of Search 53/202, 459, 567, 568, 53/570, 384, 385, 386, 469; 493/194, 195, 198

[56] References Cited

U.S. PATENT DOCUMENTS

- Re. 28,350 3/1975 Lerner 53/459
- 2,195,740 4/1940 Salfisberg 53/459 X
- 2,612,738 10/1952 Salfisberg 53/459
- 2,671,587 3/1954 Vogt 53/570 X
- 2,671,588 3/1954 Vogt 53/570 X
- 3,254,468 6/1966 Lerner 53/459

- 3,599,388 12/1968 Feingold 53/455
- 3,779,449 12/1973 Membrino 53/459 X
- 4,229,928 10/1980 Münchinger et al. 53/452
- 4,378,666 4/1983 Onishi 53/570
- 4,798,041 1/1989 Bentsen 53/459 X

FOREIGN PATENT DOCUMENTS

- 2649777 5/1978 Fed. Rep. of Germany 53/459
- 2533892 4/1984 France .

Primary Examiner—Robert L. Spruill
 Assistant Examiner—Beth Bianca
 Attorney, Agent, or Firm—Ostrolenk, Faber, Gerb & Soffen

[57] ABSTRACT

Objects are packeted in bags (5) by means of a chain (1) of flat, flexible bags being conveyed, open at the top, through a filling station (12). Each bag in the chain has a rear main wall with a lip protruding from the opening, out past the edge of the front wall (51). In the station the lip is allowed to run along a support line which, seen in the general direction of feed of the chain of bags, diverges therefrom both horizontally and vertically so that the opening of the bag (5) can easily be opened by a jet of air without creasing the chain of bags.

23 Claims, 1 Drawing Sheet

