



US009408414B2

(12) **United States Patent**
Prevost

(10) **Patent No.:** **US 9,408,414 B2**
(45) **Date of Patent:** ***Aug. 9, 2016**

(54) **ILLUMINATED CIGARETTE ROLLING AND FORMING DEVICES**

1,909,749 A	5/1933	Booth	
1,956,838 A	5/1934	Steuart	
2,009,000 A	7/1935	Zint	
2,276,719 A	3/1942	Daudelin	
2,341,375 A *	2/1944	Hambleton B25B 23/18 362/119

(71) Applicant: **David Prevost**, Portland, OR (US)

(72) Inventor: **David Prevost**, Portland, OR (US)

D142,559 S	10/1945	Herzog	
------------	---------	--------	--

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 618 days.

This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

DE	29 43 136 A1	5/1981
GB	385870 A	1/1933

(Continued)

OTHER PUBLICATIONS

Photos of prior art cigarette rolling device 1 (A-D).

(Continued)

(21) Appl. No.: **13/795,353**

(22) Filed: **Mar. 12, 2013**

(65) **Prior Publication Data**

US 2013/0192612 A1 Aug. 1, 2013

Related U.S. Application Data

(63) Continuation-in-part of application No. 13/692,875, filed on Dec. 3, 2012, now Pat. No. 9,295,283, which is a continuation-in-part of application No. 12/136,650, filed on Jun. 10, 2008, now Pat. No. 8,322,349.

(51) **Int. Cl.**

<i>A24C 5/18</i>	(2006.01)
<i>A24C 5/40</i>	(2006.01)
<i>A24C 5/44</i>	(2006.01)

(52) **U.S. Cl.**

CPC ... *A24C 5/18* (2013.01); *A24C 5/40* (2013.01);
A24C 5/44 (2013.01)

(58) **Field of Classification Search**

None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

338,580 A	3/1886	Arnold
1,087,230 A	2/1914	Garwood

Primary Examiner — Michael J Felton

(74) *Attorney, Agent, or Firm* — Schwabe, Williamson & Wyatt, P.C.

(57) **ABSTRACT**

Embodiments provide cigarette rolling and forming devices that include parallel cylinders extending between a pair of support plates, and a looped belt trained therearound. One cylinder is moveable relative to the other via a pair of curvilinear slots, and the device is configured for alternately receiving and compressing loose tobacco into a tobacco rod with the belt. In some devices, a nozzle is provided to allow longitudinal displacement of the formed tobacco rod into a pre-formed cigarette tube, and some devices include a pushing device to effect this longitudinal displacement. In some embodiments, a light source is provided and configured to illuminate a portion of the device, such as the nozzle or the recess between the cylinders. In various embodiments, the device also may include a power source configured to provide power to the light source and an activation member, such as a switch or button, configured to activate the light source.

20 Claims, 9 Drawing Sheets

