



US009409614B2

(12) **United States Patent**  
**Chang**

(10) **Patent No.:** **US 9,409,614 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

- (54) **BICYCLE SADDLE STRUCTURE**
- (71) Applicant: **Nan Kai University of Technology**,  
Nantou County (TW)
- (72) Inventor: **Teng-Ruey Chang**, Taichung (TW)
- (73) Assignee: **Nan Kai University of Technology**,  
Caotun Township (TW)
- (\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 60 days.
- (21) Appl. No.: **14/538,578**
- (22) Filed: **Nov. 11, 2014**
- (65) **Prior Publication Data**  
US 2015/0321718 A1 Nov. 12, 2015
- (30) **Foreign Application Priority Data**  
May 12, 2014 (TW) ..... 103208243 U
- (51) **Int. Cl.**  
**B62J 1/00** (2006.01)  
**B62J 1/04** (2006.01)  
**B62J 1/08** (2006.01)  
**B62J 1/02** (2006.01)
- (52) **U.S. Cl.**  
CPC .. **B62J 1/04** (2013.01); **B62J 1/005** (2013.01);  
**B62J 1/007** (2013.01); **B62J 1/02** (2013.01);  
**B62J 1/08** (2013.01)
- (58) **Field of Classification Search**  
CPC ..... B62J 1/005; B62J 1/04  
USPC ..... 297/201  
See application file for complete search history.

- (56) **References Cited**  
U.S. PATENT DOCUMENTS
- 554,337 A \* 2/1896 Dodds et al. .... B62J 1/02  
297/201
- 633,487 A \* 9/1899 Radermacher ..... B62J 1/005  
297/201
- 4,877,286 A \* 10/1989 Hobson ..... B62J 1/002  
297/201
- 5,352,016 A \* 10/1994 Hobson ..... B62J 1/10  
297/201
- 5,823,618 A \* 10/1998 Fox ..... B62J 1/005  
297/195.1
- 5,911,474 A \* 6/1999 Lee ..... B62J 1/005  
297/201
- 6,074,002 A \* 6/2000 Hansen ..... B62J 1/002  
297/201
- 6,113,184 A \* 9/2000 Barnes ..... B62J 1/007  
297/197
- 6,209,954 B1 \* 4/2001 Bombardier ..... B62J 1/005  
297/201
- 6,575,529 B1 \* 6/2003 Yu ..... B62J 1/10  
297/201

(Continued)

*Primary Examiner* — David E Allred  
*Assistant Examiner* — Alexander Harrison  
(74) *Attorney, Agent, or Firm* — Wang Law Firm, Inc.

(57) **ABSTRACT**  
A bicycle saddle structure includes a saddle portion having two elastic supporting bodies in a bottom surface thereof and a nose position pivoted to the saddle portion, the elastic supporting bodies are circular spiral-shaped, which can provide a buffer force to the rider, so as to improve the riding comfort. The nose portion can be selectively located at the same level as or vertical to the saddle portion via a pivoting unit, the saddle can be changed to the nose-shaped saddle or the saddle without nose portion, so as to improve the applicability.

**11 Claims, 17 Drawing Sheets**

