



(12) **United States Patent**  
**Cieřlikowski et al.**

(10) **Patent No.:** **US 9,408,415 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **METHOD AND UNIT FOR UNEVEN TRANSFERRING OF BEADS**  
(71) Applicant: **International Tobacco Machinery Poland Sp. z o.o.**, Radom (PL)  
(72) Inventors: **Bartosz Cieřlikowski**, Radom (PL); **Radosław Figarski**, Radom (PL); **Jacek Figarski**, Radom (PL); **Kazimierz Makosa**, Radom (PL)  
(73) Assignee: **International Tobacco Machinery Poland sp.z.o.o.**, Radom (PL)  
(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 547 days.

(21) Appl. No.: **13/924,663**  
(22) Filed: **Jun. 24, 2013**

(65) **Prior Publication Data**  
US 2014/0011652 A1 Jan. 9, 2014

(30) **Foreign Application Priority Data**  
Jul. 4, 2012 (PL) ..... 399794

(51) **Int. Cl.**  
**A24D 3/02** (2006.01)  
**B65G 47/14** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **A24D 3/02** (2013.01); **A24D 3/0216** (2013.01); **B65G 29/02** (2013.01); **B65G 47/1428** (2013.01); **B65G 47/846** (2013.01)

(58) **Field of Classification Search**  
CPC ..... A24D 3/00; A24D 3/02; A24D 3/04; A24D 3/0216; A24D 3/061; A24D 3/0229; A24D 3/0241; B65G 29/02; B65G 47/1428; B65G 47/846-47/848  
USPC ..... 493/39, 44, 45, 47-50; 198/396, 198/397.01, 397.04, 397.05; 221/1, 7, 68, 221/72, 211, 265, 277, 282

See application file for complete search history.

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
2,991,871 A \* 7/1961 Lupo ..... B65G 47/1421 198/723  
3,599,781 A \* 8/1971 Hoadley ..... B65G 29/00 198/719  
(Continued)

**FOREIGN PATENT DOCUMENTS**  
CN 1972606 B 5/2007  
CN 101765379 A 6/2010  
(Continued)

**OTHER PUBLICATIONS**  
Chinese search report in counterpart application CN2013102746252 filed Jul. 2, 2013.  
(Continued)

*Primary Examiner* — Hemant M Desai  
*Assistant Examiner* — Valentin Neacsu  
(74) *Attorney, Agent, or Firm* — Oppedahl Patent Law Firm LLC

(57) **ABSTRACT**  
A unit for uneven transferring of a bead (2) stream in a filter manufacturing machine, from receiving pockets (18) to leading away pockets (21), through guiding grooves disposed on guiding plates, comprising two guiding plates (5, 6) situated on top of each other, whereas a guiding groove (5A) of the first guiding plate (5) and a guiding groove (6A) of the second guiding plate (6) intersect, forming at least one bead (2) guiding chamber, whereas at least one of the guiding plates (5, 6) is movable, wherein the receiving pockets (18) and the leading away pockets (21) are disposed along the circumference of the guiding plates (5, 6) so that the distances (S1, S2, T1, T2) between the successive pockets (18, 21) are alternately different.

**4 Claims, 7 Drawing Sheets**

