



(12) **United States Patent**
Salter et al.

(10) **Patent No.:** **US 9,409,515 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **LUMINESCENT SEATING ASSEMBLY**

F21V 9/16 (2013.01); *H05B 37/0218*
(2013.01); *H05B 37/0227* (2013.01); *F21Y*
2101/02 (2013.01); *Y02B 20/46* (2013.01)

(71) Applicant: **Ford Global Technologies, LLC,**
Dearborn, MI (US)

(58) **Field of Classification Search**
CPC B60Q 3/001; B60Q 3/008; B60Q 3/0223;
B60Q 3/0243; B60Q 3/0293; F21V 9/16;
H05B 37/0218; H05B 37/0227
USPC 362/487-488, 509-510
See application file for complete search history.

(72) Inventors: **Stuart C. Salter,** White Lake, MI (US);
James J. Surman, Clinton Township,
MI (US); **Cornel Lewis Gardner,**
Romulus, MI (US)

(73) Assignee: **Ford Global Technologies, LLC,**
Dearborn, MI (US)

(56) **References Cited**

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

U.S. PATENT DOCUMENTS

(21) Appl. No.: **14/719,042**

4,702,519	A	10/1987	Labanoff
6,394,551	B1	5/2002	Beukema
6,729,738	B2	5/2004	Fuwausa et al.
6,773,129	B2	8/2004	Anderson, Jr. et al.
6,871,986	B2	3/2005	Yamanaka et al.
6,990,922	B2	1/2006	Ichikawa et al.

(22) Filed: **May 21, 2015**

(Continued)

(65) **Prior Publication Data**

FOREIGN PATENT DOCUMENTS

US 2015/0251596 A1 Sep. 10, 2015

CN	201169230	Y	2/2009
CN	201193011	Y	2/2009

Related U.S. Application Data

(Continued)

(63) Continuation-in-part of application No. 14/603,636,
filed on Jan. 23, 2015, which is a continuation-in-part
of application No. 14/086,442, filed on Nov. 21, 2013.

Primary Examiner — Jason Moon Han

(74) *Attorney, Agent, or Firm* — Vichit Chea; Price
Heneveld LLP

(51) **Int. Cl.**

(57) **ABSTRACT**

<i>B60Q 1/00</i>	(2006.01)
<i>B60Q 1/26</i>	(2006.01)
<i>B60Q 3/02</i>	(2006.01)
<i>F21V 9/16</i>	(2006.01)
<i>H05B 37/02</i>	(2006.01)
<i>B60Q 3/00</i>	(2006.01)
<i>F21Y 101/02</i>	(2006.01)

A lighting system for a vehicle headrest is provided herein.
The lighting system includes a support attached to a headrest
on a first end and removably coupled to a seatback on the
opposing end. A light source is disposed on the headrest. A
first photoluminescent structure is disposed within the system
and is configured to luminesce in response to excitation by the
light source. The light source may comprise a plurality of
printed LEDs employing a thin configuration.

(52) **U.S. Cl.**

CPC *B60Q 3/0223* (2013.01); *B60Q 3/001*
(2013.01); *B60Q 3/008* (2013.01); *B60Q*
3/0243 (2013.01); *B60Q 3/0293* (2013.01);

20 Claims, 12 Drawing Sheets

