United States Patent [19]

Hatuse et al.

[11] **4,257,115**

[45] **Mar. 17, 1981**

[54] **SWITCH STRUCTURE FOR ELECTRONIC TIMEPIECE**

[75] Inventors: **Toshikazu Hatuse**, Tanashi; **Minoru Natori**, Tokyo; **Toshikazu Shimazaki**, Tanashi; **Kouhei Kawanobe**, Kawagoe; **Hiroshi Ogawa**, Tokorozawa, all of Japan

[73] Assignee: **Citizen Watch Co., Ltd.**, Tokyo, Japan

[21] Appl. No.: **876,733**

[22] Filed: **Feb. 10, 1978**

[30] **Foreign Application Priority Data**

Feb. 12, 1977 [JP] Japan 52/14369
Mar. 7, 1977 [JP] Japan 52/23885

[51] **Int. Cl.**[3] **G04C 17/00**; G04B 23/02; G04B 19/04

[52] **U.S. Cl.** **368/69**; 368/74; 368/80; 368/82; 368/232; 368/251

[58] **Field of Search** ..... 58/23 R, 50 R, 57.5, 58/85.5, 152 R, 152 B, 127 R, 127 B; 200/DIG. 1; 340/324 R, 324 M, 712

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,757,322	9/1973	Barkan	200/DIG. 1
3,813,533	5/1974	Cone	58/50 R
3,945,191	3/1976	van Berkum	58/50 R
4,017,848	4/1977	Tannas	340/324 M
4,055,755	10/1977	Nakamura	58/152 R
4,077,032	2/1978	Volkman	58/50 R
4,091,610	5/1978	Sasaki	200/DIG. 1
4,120,036	10/1978	Maeda	58/152 R

Primary Examiner—Vit W. Miska

[57] **ABSTRACT**

A switch structure for an analog quartz crystal timepiece having a watchglass plate, a time dial to display time in an analog mode, and a digital display device, which switch structure comprises a plurality of transparent electrically conductive electrode films provided on the watchglass plate at positions corresponding to numerical display indicia on the time dial to permit generation of input signals corresponding to the numerical display indicia, respectively.

2 Claims, 8 Drawing Figures