US009409616B2

(12) **United States Patent**
Lu et al.

(10) **Patent No.: US 9,409,616 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **RIDING VEHICLE WITH SELF-CORRECTING STEERING**

(71) Applicant: **Prince Lionheart, Inc.**, Santa Maria, CA (US)

(72) Inventors: **Yafei Lu**, Jiangsu (CN); **Jing Jing Pi**, Jiangsu (CN); **Thomas E McConnell**, Santa Ynez, CA (US)

(73) Assignee: **Prince Lionheart, Inc.**, Santa Maria, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/256,773**

(22) Filed: **Apr. 18, 2014**

(65) **Prior Publication Data**

US 2014/0312587 A1 Oct. 23, 2014

Related U.S. Application Data

(63) Continuation of application No. 29/454,309, filed on May 8, 2013, now Pat. No. Des. 732,609.

(60) Provisional application No. 61/813,590, filed on Apr. 18, 2013.

(51) **Int. Cl.**
B62K 21/02 (2006.01)
B62K 9/00 (2006.01)

(52) **U.S. Cl.**
CPC ***B62K 9/00*** (2013.01)

(58) **Field of Classification Search**
CPC B62K 3/002; B62K 21/00; B62K 21/10; B62K 9/00; A63C 17/012
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

600,046	A *	3/1898	Sparks	B62K 21/10	280/271
4,394,029	A *	7/1983	Holmgren	A63C 17/045	280/11.223
4,674,761	A *	6/1987	Kassai	B62K 9/02	280/271
4,714,261	A *	12/1987	Kassai	A63H 17/36	280/267
6,378,884	B1 *	4/2002	Kettler	B29C 44/485	280/272
6,520,517	B1 *	2/2003	Chung	B62K 21/00	280/124.11
6,572,130	B2 *	6/2003	Greene, Jr.	B62K 3/005	280/266
6,616,155	B2 *	9/2003	Tuan	A63C 17/01	280/11.28
6,669,215	B2 *	12/2003	Laporte	A63C 17/01	280/124.11
7,226,081	B2 *	6/2007	Chen	B62K 21/00	280/263
7,243,931	B2 *	7/2007	Chen	B62K 3/002	280/124.11

(Continued)

Primary Examiner — Brodie Follman
(74) *Attorney, Agent, or Firm* — WPAT, P.C., Intellectual Property Attorneys; Anthony King

(57) **ABSTRACT**

A children's ride-on vehicle with a self-straightening mechanism/feature directed to self-correct or self-straighten the steering of the vehicle as it crosses varying types and conditions of terrain. The vehicle includes a main body, a front shaft connector to connect at least one wheel to the main body, a rear shaft connector to connect at least one rear wheel to the main body; and providing a spring piece to resiliently bias at least one of said front and rear shaft connector into a specified position.

11 Claims, 16 Drawing Sheets