US005804917A

United States Patent [19]

Takahashi et al.

[11] **Patent Number: 5,804,917**

[45] **Date of Patent: Sep. 8, 1998**

[54] **ORGANIC ELECTROLUMINESCENT DISPLAY DEVICE AND METHOD FOR MANUFACTURING SAME**

[75] Inventors: **Hisamitsu Takahashi**; **Yoshihisa Tsuruoka**; **Toshio Miyauchi**; **Shigeru Hieda**, all of Mobara, Japan

[73] Assignee: **Futaba Denshi Kogyo K.K.**, Mobara, Japan

[21] Appl. No.: **593,972**

[22] Filed: **Jan. 30, 1996**

[51] **Int. Cl.**[6] **H05B 33/02**

[52] **U.S. Cl.** **313/504**; 313/503; 313/505; 313/500

[58] **Field of Search** 313/500, 503, 313/504, 505, 512, 509; 315/169.1, 169.3

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,015,166	3/1977	Ohshima et al.	313/503
4,692,662	9/1987	Wada et al.	313/587
4,803,402	2/1989	Raber et al.	313/587
4,843,281	6/1989	Mendelsohn	313/587
5,053,679	10/1991	Thioulouse	313/512
5,276,380	1/1994	Tang	313/505
5,302,468	4/1994	Namiki et al.	313/504
5,634,836	6/1997	Lepselter	313/587

Primary Examiner—Sandra L. O'Shea
Assistant Examiner—Joseph Williams
Attorney, Agent, or Firm—Oblon, Spivak, McClelland, Maier & Neustadt, P.C.

[57] **ABSTRACT**

An organic electroluminescent display device capable of permitting upper electrodes of a fine pattern to be formed and exhibiting increased durability. Ribs are spaced at predetermined intervals on transparent electrodes arranged in the form of a film on a lower transparent substrate. An organic layer is formed between each adjacent two of the ribs and an upper electrode is deposited all over the transparent electrodes. A portion of the upper electrode formed on each of the ribs is removed by scraping, rubbing or the like, resulting in the upper electrode being formed on only each of the organic layers. A cap layer may be provided on the upper electrode as required.

7 Claims, 7 Drawing Sheets