

(12) **United States Patent**
Johnston et al.

(10) **Patent No.:** **US 9,408,718 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **INTER-VERTEBRAL IMPLANT WITH ANGLED PLATE**

USPC 623/17.11-17.16; 606/912
See application file for complete search history.

(75) Inventors: **Terry Johnston**, San Carlos, CA (US);
Fred H. Geisler, Aurora, IL (US)

(56) **References Cited**

(73) Assignee: **RHAUSLER, INC.**, San Carlos, CA (US)

U.S. PATENT DOCUMENTS

5,425,772 A 6/1995 Brantigan
5,766,252 A 6/1998 Henry et al.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **13/538,039**

EP 18472040 A1 10/2007
WO 2007038545 A1 4/2007
WO 2008154326 A1 12/2008

(22) Filed: **Jun. 29, 2012**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2012/0316649 A1 Dec. 13, 2012

International Search Report and Written Opinion and related PCT/US2011/020053, dated Sep. 22, 2011.

(Continued)

Related U.S. Application Data

(63) Continuation-in-part of application No. 12/650,600, filed on Dec. 31, 2009, now Pat. No. 8,945,226.

Primary Examiner — Christian Sevilla

Assistant Examiner — Eric S Gibson

(74) *Attorney, Agent, or Firm* — Kramer Amado, P.C.

(51) **Int. Cl.**

A61F 2/44 (2006.01)
A61F 2/28 (2006.01)
A61F 2/30 (2006.01)

(57) **ABSTRACT**

An inter-vertebral implant having a hollow frame having a top load bearing surface and a bottom load bearing surface may be inserted between a first spinal vertebra and a second spinal vertebra. The top load bearing surface and the bottom load bearing surface may each include an opening allowing access to the interior of the frame. A front surface may extend between the top load bearing surface and the bottom load bearing surface, and a rear surface may extend between the top load bearing surface and the bottom load bearing surface. A plate is attached to the front surface of the support device. The interior front plate may be arranged along a plane (P), and an axis (A) between the top load bearing surface and the bottom load bearing surface may be at a non-right angle relative to the plane (P).

(52) **U.S. Cl.**

CPC *A61F 2/447* (2013.01); *A61F 2/442* (2013.01); *A61F 2002/2817* (2013.01); *A61F 2002/2835* (2013.01); *A61F 2002/3008* (2013.01); *A61F 2002/30056* (2013.01); *A61F 2002/30271* (2013.01); *A61F 2002/30448* (2013.01); *A61F 2002/30576* (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC *A61F 2/447*; *A61F 2/44*; *A61F 2/4455*; *A61F 2/446*; *A61F 2/4465*; *A61F 2002/4475*; *A61F 2002/448*; *A61F 2002/4485*; *A61F 2002/449*; *A61B 17/7059*

27 Claims, 10 Drawing Sheets

