



US009410518B2

(12) **United States Patent**  
**Geyer et al.**

(10) **Patent No.:** **US 9,410,518 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **TAPPET**

(71) Applicant: **Schaeffler Technologies AG & Co. KG**,  
Herzogenaurach (DE)

(72) Inventors: **Norbert Geyer**, Hochstadt (DE); **Stefan Dorn**, Hollfeld (DE)

(73) Assignee: **Schaeffler Technologies AG & Co. KG**,  
Herzogenaurach (DE)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/763,688**

(22) PCT Filed: **Nov. 18, 2013**

(86) PCT No.: **PCT/DE2013/200304**

§ 371 (c)(1),

(2) Date: **Jul. 27, 2015**

(87) PCT Pub. No.: **WO2014/117762**

PCT Pub. Date: **Aug. 7, 2014**

(65) **Prior Publication Data**

US 2015/0361937 A1 Dec. 17, 2015

(30) **Foreign Application Priority Data**

Jan. 29, 2013 (DE) ..... 10 2013 201 335

(51) **Int. Cl.**

**F16H 53/06** (2006.01)

**F01L 1/14** (2006.01)

**F02M 59/10** (2006.01)

**F04B 1/04** (2006.01)

(52) **U.S. Cl.**

CPC ..... **F02M 59/102** (2013.01); **F04B 1/0408**  
(2013.01); **F04B 1/0426** (2013.01); **F04B**  
**1/0435** (2013.01); **F04B 1/0439** (2013.01)

(58) **Field of Classification Search**

CPC ... F02M 59/102; F04B 1/0408; F04B 1/0426;  
F04B 1/0435; F04B 1/0439; F01L 1/14;  
F01L 1/143; F01L 2001/187; Y10T 74/2107  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,793,583 B2 \* 9/2010 Radinger ..... F01L 1/143  
74/569  
8,201,532 B2 \* 6/2012 Prokop ..... F01L 1/14  
123/90.5  
8,522,739 B2 \* 9/2013 Pflugl ..... F01L 1/14  
123/90.48

(Continued)

FOREIGN PATENT DOCUMENTS

DE 102012211113 1/2014  
DE 102012211529 A1 \* 1/2014 ..... F01L 1/14  
WO 2008068116 6/2008

Primary Examiner — Adam D Rogers

(74) Attorney, Agent, or Firm — Volpe and Koenig, P.C.

(57) **ABSTRACT**

A tappet including a housing having a drive-side annular end face at which two flat sections, recessed in relation to an outer shell of the housing, lie diametrically opposite one another, and a bolt supporting a roller mounted in said sections is provided. A bridge section protrudes through an inner shell of the housing, and the output-side end face of said bridge section acts as a contact point for a tappet follower part, the bridge section lying against undersides of said flat sections and being held by a ring that is arranged in the inner shell, and sits in a groove of the inner shell so as not to protrude radially out of said groove, at least two tabs projecting radially inwards from an upper side of the ring, and the bridge section fixed thereupon in the direction of the output-side annular end face.

**8 Claims, 3 Drawing Sheets**

