US009411118B2

(12) **United States Patent**
Matz et al.

(10) **Patent No.: US 9,411,118 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **FIBER DISTRIBUTION HUBS AND STORAGE RETAINING MODULES**

(71) Applicant: **Opterna Technology Limited**, Limerick (IE)

(72) Inventors: **Bret A. Matz**, Leesburg, VA (US); **Benoy Sarasan**, Kochi (IN); **Beevi M. Mohammedali**, Kochi (IN); **P. V. Ashwin**, Kochi (IN); **C. S. Subash**, Kochi (IN)

(73) Assignee: **Opterna Technology Limited**, Limerick (IE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/248,835**

(22) Filed: **Apr. 9, 2014**

(65) **Prior Publication Data**

US 2014/0301709 A1 Oct. 9, 2014

Related U.S. Application Data

(60) Provisional application No. 61/810,175, filed on Apr. 9, 2013.

(51) **Int. Cl.**
G02B 6/00 (2006.01)
G02B 6/44 (2006.01)

(52) **U.S. Cl.**
CPC ***G02B 6/4452*** (2013.01)

(58) **Field of Classification Search**
USPC 385/135
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,190,874	B1 *	3/2007	Barth et al.	385/135
2006/0269204	A1 *	11/2006	Barth et al.	385/135
2009/0110359	A1 *	4/2009	Smith	G02B 6/445 385/135
2011/0211799	A1 *	9/2011	Conner et al.	385/135
2014/0314384	A1 *	10/2014	Nair et al.	385/135

* cited by examiner

Primary Examiner — Eric Wong
(74) *Attorney, Agent, or Firm* — Sterne, Kessler, Goldstein & Fox P.L.L.C.

(57) **ABSTRACT**

A fiber distribution hub (FDH) can include an enclosure defining an interior region and a frame body having a longitudinal axis. The frame body is rotatably mounted within the interior region of the enclosure such that the frame body can rotate about the longitudinal axis relative to the enclosure. The FDH further includes a plurality of splitters coupled to the frame body. Each splitter module has at least one splitter input and at least two splitter outputs. The FDH also includes a first plurality of adapters coupled to the frame body. The first plurality of adapters is configured to optically couple to splitter output cables. Additionally, the FDH can also include a storage retaining module configured to be selectively coupled to the frame body. The storage retaining module includes a storage retaining structure configured to selectively secure a cable portion of a connectorized end of a splitter output cable.

25 Claims, 14 Drawing Sheets