

7

plication of the cap to a bottle, and a peripheral shoulder above the locking rib having a diameter greater than the diameter of the locking rib but less than the diameter of the inner wall prior to the reclosure cap being fixedly attached to a bottle lip.

10 A bottle reclosure cap comprising a cap body including an end wall and a depending peripheral skirt of polymeric material, said peripheral skirt having an inner peripheral wall defining an internal cavity adapted to receive therein a bottle lip, an inwardly directed peripheral metallic locking rib carried by said skirt in spaced relationship to said end wall, said rib being relatively non-resilient but readily deformable, a gasket in said cap body in spaced relation to said rib, said gasket being formed of resilient material, a peripheral shoulder above the locking rib having a diameter greater than the diameter of the locking rib but less than the diameter of the inner wall to locate a bottle lip in the cavity and prevent side forces from dislodging said cap from a bottle, said shoulder including an inclined face opposing said end wall,

8

and said end wall being recessed to define a chamber into which said gasket is deformed upon the application of the cap to a bottle.

References Cited by the Examiner

UNITED STATES PATENTS

810,736	1/1906	Fenn	215—45
1,372,007	3/1921	Liarson et al.	215—46
1,739,759	12/1929	Hothersall	220—45
2,263,653	11/1941	Smith et al.	215—40
2,582,489	1/1952	Krueger	215—38
2,647,652	8/1953	Sanford	215—40
2,953,272	9/1960	Mumford et al.	215—41
3,122,254	2/1964	Hagmann	215—39

FOREIGN PATENTS

506,708 10/1954 Canada.

JOSEPH R. LECLAIR, *Primary Examiner*.

J. F. McNULTY, D. F. NORTON, *Assistant Examiners*.