

## CORDLESS PULSE OXIMETER

## BACKGROUND AND SUMMARY OF THE INVENTION

The invention relates to a cordless finger sensor for measuring blood oxygen saturation. More particularly, the present invention provides a module that fits into a special recess within an oximeter so that when in use, it becomes an integral part of the instrument. The invention allows for removal and replacement of the sensing module in case of component failure. Elimination of the sensor cable makes for easier carrying and storage of the device.

A small cordless oximeter in which all of the electronics are contained within the finger-gripping means is described in U.S. Pat. No. 5,490,523 to Isaacson et al. This device eliminates the external cord of a conventional oximeter and securely holds the patient's finger without support from the operator. Its external spring and lack of an internal pivot point prevent it from being used inside other devices. The design of the Isaacson oximeter also prevents the average user from replacing the sensor components in case of failure. In the event of LED or photodetector malfunction, the entire device is usually replaced.

A pulse oximeter with both replaceable and reusable components is taught by Swedlow et al in U.S. Pat. No. 5,209,250. Their device uses a conventional cord to connect the sensor to an oximeter. The replaceable part, containing only the LEDs, is wrapped over the end of the finger. The sensor has laterally extending adhesive webs which are then folded around the finger to hold the sensor in place.

Tobler et al in U.S. Pat. No. 5,645,440 describe a novel connector for oximeter sensors. This invention, assigned to Masimo, allows the user to quickly discard a disposable sensor at the end of a conventional cable and replace it with another one.

The sensor to be described eliminates the need for a separate finger sensor with its attendant cable. The sensor allows the insertion of any adult finger and that of children down to the age of about three. During use it is an integral part of the surrounding oximeter but can be readily removed and replaced by the user in the event of failure of the LEDs or photodetector. Its design enables it to be used with a variety of instruments from small saturation-only devices to larger multi-parameter instruments which can also measure temperature, end-tidal CO<sub>2</sub> or blood pressure.

A primary object of the invention is to provide a sensing module with the sensor having its own internal spring for gripping various size fingers, from those of large adults to children as young as three years of age.

A further object of the invention is to provide a sensing module which slides into a recess within an oximeter so that it is an integral part of the oximeter without the need for any external cords or cables.

Another object of the invention is to provide a sensing module which fits within the oximeter recess so securely that no special screws or latches are needed to hold it in place.

A further object of the invention is to provide a sensing module that can be used in many different types of monitoring devices. These can be small saturation-only instruments, devices measuring saturation and temperature, or devices measuring saturation, expired CO<sub>2</sub> or blood pressure.

Other objects and advantages of the invention will become apparent from the following description and drawings wherein:

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows the sensing module as used in a miniature pulse oximeter;

FIG. 2 shows the sensor being opened to allow insertion of a subject's finger;

FIG. 3 shows the method by which the sensing module is removed from or inserted into the oximeter;

FIG. 4 is a top view of the upper fingertip enclosure which pivots and contains the LED assembly;

FIG. 5 is an internal view of the same fingertip cover of FIG. 4;

FIG. 6 is a view looking downward at the enclosure for the lower fingertip pad, showing the internal spring, the dual row pin connector and the side rails which stabilize this portion of the sensor when it is placed into the oximeter;

FIG. 7 shows the top surface of the lower enclosure and the placement of the photodetector;

FIG. 8 is a view of the assembled sensor module;

FIG. 9 is an expanded view of a disassembled sensor module showing the four major plastic parts and two circuit boards of which it is comprised;

FIG. 10 shows a combination saturation and temperature monitor which uses the sensing module of the present invention.

## DETAILED DESCRIPTION OF THE DRAWINGS

FIGS. 1-3 show a cordless miniature oximeter using the replaceable sensing module of the present invention. The body portion 20 carries an internal power supply, consisting of a single AAA battery, as well as pulse oximetry circuitry and memory. Circuitry and signal processing methods for pulse oximetry are now well known in the art.

Other aspects of the miniature pulse oximeter shown in FIGS. 1 & 2 are the LCD display 30, control buttons 27, 28 & 29 and the sensing module 80. FIG. 2 shows the movable top portion 70 of the module 80 being opened by the operator's finger 8 with pressure on knob 79 which stretches internal spring 92 (FIG. 7). When the operator's finger is lifted, tension of the internal spring causes a moderate gripping pressure on the patient's finger situated inside the sensor. LED's 85 (FIG. 9) are centrally mounted on the underside of the upper lid and a photodetector 86 (FIG. 9) is located in a directly opposite position facing upward on the lower fingertip pad 50. As shown in FIG. 3, the removable sensing module 80 is carried in a recess between arms 42 and 43 of body portion 20 by means of horizontal rails 51 & 52 that slide into reciprocal grooves 53 & 54, carried by arms 42 & 43, respectively. The rails may alternately be formed on arms 42 and 43 and reciprocal grooves formed on sensing module 80. Electrical connector pins 55 (FIG. 6) extend rearwardly from sensing module 80 and slidably engage electrical multi-pin socket 56 (FIG. 3) carried by oximeter body portion 20. Connector pins 55 and socket 56 allow the sensing module to be detachably connected to the electronic circuitry of the oximeter. The connector pins 55 and socket 56 also create a mechanical connection between the sensing module 80 and oximeter body 20, effectively preventing dislodgement of the attached sensing module. Sensing module 80 can be readily removed and replaced by a user without using any tools.

Fingertip pad 50 and fingertip cover 70 have concave surfaces 75 and 77, respectively with curvatures comfortable for the fingertip of an average adult user. Children as young as three can also utilize the sensor. A subject's finger is