



US009408520B2

(12) **United States Patent**
Vacca et al.

(10) **Patent No.:** **US 9,408,520 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **INVERTIBLE DISHWASHING RACK AND RELATED METHODS**

(71) Applicants: **Rosario Vacca**, Murrieta, CA (US);
Ronald L. Pawlak, Tucson, AZ (US)

(72) Inventors: **Rosario Vacca**, Murrieta, CA (US);
Ronald L. Pawlak, Tucson, AZ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 544 days.

(21) Appl. No.: **13/781,604**

(22) Filed: **Feb. 28, 2013**

(65) **Prior Publication Data**
US 2013/0233353 A1 Sep. 12, 2013

Related U.S. Application Data
(60) Provisional application No. 61/605,356, filed on Mar. 1, 2012.

(51) **Int. Cl.**
B08B 3/00 (2006.01)
A47L 15/50 (2006.01)
A47L 15/00 (2006.01)

(52) **U.S. Cl.**
CPC **A47L 15/50** (2013.01); **A47L 15/501** (2013.01); **A47L 15/0076** (2013.01); **Y10T 29/49826** (2015.01)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2006/0119236 A1* 6/2006 Dickson A47L 15/504
312/311
2011/0064549 A1* 3/2011 Carpinelli A47L 15/501
414/405

* cited by examiner

Primary Examiner — Eric Golightly

(74) *Attorney, Agent, or Firm* — Acuity Law Group, P.C.;
Daniel M. Chambers

(57) **ABSTRACT**

A substantially rectangular dish rack having a substantially single side walled body portion that slidably engages two identical base portions, which interchangeably function as either the top or bottom of the dish rack. The top and bottom portions are preferably both inserted into the body portion from the same side of the body portion. Any of the four sides of the top and bottom portions may be inserted first into the body portion, and when inserted into the body portion, the base portions are held in place by friction catches or latches. The friction latches preferably include a boss portion and a notch portion to receive the boss portion. Alternative embodiments include designated top and bottom portion and are color coded to signal the identity of each. The body portion is preferably constructed to allow for extension of the body portion to allow for different heights of dishwares, by collars which are attachable and detachable to and from the body portion by prongs and sockets, which mutually engage on another.

7 Claims, 24 Drawing Sheets

