

11

1. A label assembly for an electronic device, comprising:
 - a flexible body with a front surface and a back surface, including a first end and a second end, the first end including a first attachment area with an electrical connector attached to the electronic device, the second end including a second attachment;
 - a label attached to the front surface of the flexible body including a visual representation of a connection of the electronic device that corresponds to an actual connection of the electronic device and includes an identification mark associated with the visual representation of the connection;
 - the flexible body including a status indicator that presents a status, wherein the status is a condition of the actual connection of the electronic device based on electrical signals received by the status indicator, from the electronic device; and
 - the electrical connector connecting the status indicator of the flexible body and the electrical signals associated with the actual connection of the electronic device.
2. The label assembly of claim 1, wherein the flexible body is retractably attached to a retracting device.
3. The label assembly of claim 2, wherein the second attachment area of the flexible body is retractably attached to the retracting device, the label and the flexible body forming a spiral orientation within the retracting device, when retracted.
4. The label assembly of claim 2, wherein the first attachment area of the flexible body is retractably attached to the retracting device, the retracting device is attached to the electronic device, and the label and the flexible body forming a spiral orientation within the retracting device, when retracted.
5. The label assembly of claim 1, wherein the front of the flexible body includes a label detachably attached to the flexible body, and the back of the flexible body is blank.
6. The label assembly of claim 1, wherein the back of the flexible body includes a second label, wherein the second label includes one or both of: information associated with the electronic device and information associated with components within the electronic device.
7. The label assembly of claim 1, wherein the status indicator is an LED (light emitting diode) that indicates the status of the actual connection of the electronic device.
8. The label assembly of claim 7, wherein the LED indicates the status of the actual connector of the electronic device based on displaying one or a more of: a steady light, a pattern of blinking light, an absence of light.
9. The label assembly of claim 1, wherein the status indicator is comprised of an LCD (liquid crystal display) that indicates one or both of: the identification mark associated with the visual representation of the connection and the status of the actual connection of the electronic device.

12

10. The label assembly of claim 9, wherein the LCD indicates one or both of: the identification mark associated with the visual representation of the connection and the status of the actual connection of the electronic device based on displaying one or more of: flashing, text, one or more numerals, a streaming message, a graphic.
11. The label assembly of claim 1, wherein the status indicator is comprised of an RFID tag (radio-frequency identification tag) that indicates one or both of: the identification mark associated with the visual representation of the connection and the status of the actual connection of the electronic device.
12. The label assembly of claim 11, wherein the RFID tag indicates one or both of: the identification mark associated with the visual representation of the connection and the status of the actual connection of the electronic device based on one or more of: a radio frequency message including a connector ID, a status code, an error code.
13. The label assembly of claim 1, wherein the flexible body is comprised of a material having dielectric properties for insulating low voltage circuitry.
14. The label assembly of claim 1, wherein the flexible body is comprised of polyimide material.
15. The label assembly of claim 1, wherein the label is a photo image of the actual connection of the electronic device.
16. The label assembly of claim 15, wherein the label includes one or more markings added to the photo image of the actual connection of the electronic device.
17. The label assembly of claim 1, wherein the label is removable from attachment to the flexible body by using corresponding hook-and-loop fasteners, one corresponding hook-and-loop fastener attached to the label and another corresponding hook-and-loop fastener attached to the flexible body.
18. The label assembly of claim 1, wherein the status indicator displaying a status based on the electrical signals associated with the actual connection of the electronic device is attached to electronic circuitry of the flexible body and visibly free of coverage by the label attached to the front surface of the flexible body.
19. The label assembly of claim 1, wherein the electrical connector provides an electrical signal to the status indicator, associated with a status of the actual connection of the electronic device.
20. The label assembly of claim 1, wherein the status indicator is an electronic speaker, the electronic speaker indicating one or both of: the identification mark associated with the visual representation of the connection and the status of the actual connection of the electronic device, based on an audio presentation including one or more of: synthesized or recorded language, sounds, and codes.

* * * * *