



US009409721B2

(12) **United States Patent**  
**Musick et al.**

(10) **Patent No.:** **US 9,409,721 B2**  
(45) **Date of Patent:** **\*Aug. 9, 2016**

(54) **CONVEYOR SYSTEM WEAR INDICATION DEVICES AND METHODS**

(71) Applicant: **Solus Industrial Innovations, LLC**,  
Florence, KY (US)

(72) Inventors: **Scott Musick**, Alexandria, KY (US);  
**Bruce Wagner**, Arnold, MD (US)

(73) Assignee: **Solus Industrial Innovations, LLC**,  
Florence, KY (US)

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-  
claimer.

(21) Appl. No.: **14/795,520**

(22) Filed: **Jul. 9, 2015**

(65) **Prior Publication Data**

US 2016/0009500 A1 Jan. 14, 2016

**Related U.S. Application Data**

(63) Continuation of application No. 14/061,630, filed on  
Oct. 23, 2013, now Pat. No. 9,102,476.

(60) Provisional application No. 61/718,669, filed on Oct.  
25, 2012.

(51) **Int. Cl.**

**B65G 15/62** (2006.01)  
**B65G 43/00** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **B65G 43/00** (2013.01); **B65G 17/086**  
(2013.01); **B65G 21/22** (2013.01); **B65G**  
**2207/48** (2013.01); **B65G 2812/02069**  
(2013.01)

(58) **Field of Classification Search**

CPC ..... B65G 15/62; B65G 21/22; B65G 17/086;  
B65G 2207/48

USPC ..... 198/831, 837, 841  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,996,586 A 4/1935 Meyer  
2,234,537 A 3/1941 Blackburn  
2,906,395 A 9/1959 Greer

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2327646 6/2002  
CA 2411869 5/2004

(Continued)

OTHER PUBLICATIONS

Re-Examination Application No. 95/000,071, filed Jan. 26, 2005,  
Guldenfels.

(Continued)

*Primary Examiner* — James R Bidwell

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson &  
Bear, LLP

(57) **ABSTRACT**

A wear-indicating conveyor track including an upper surface  
configured to interface with a moveable conveyor and one or  
more indicators disposed on or in at least the upper surface of  
the track. The one or more indicators can be configured to be  
substantially obscured by a conveyor placed on the track upon  
initial use, and the one or more indicators can be configured to  
be substantially unobscured by the conveyor when the con-  
veyor is moving relative to the track and the track is in need of  
repair or replacement.

**20 Claims, 8 Drawing Sheets**

