



US009510821B2

(12) **United States Patent**
Denham et al.

(10) **Patent No.:** **US 9,510,821 B2**
(45) **Date of Patent:** **Dec. 6, 2016**

(54) **METHOD AND APPARATUS FOR COUPLING ANATOMICAL FEATURES**

2002/00864;A61F 2002/0882; A61F
2002/0888; A61F 2002/0852; A61F
2002/0829

(71) Applicant: **Biomet Sports Medicine, LLC,**
Warsaw, IN (US)

See application file for complete search history.

(72) Inventors: **Gregory J. Denham,** Warsaw, IN (US);
Kevin T. Stone, Winona Lake, IN (US)

(56) **References Cited**

(73) Assignee: **Biomet Sports Medicine, LLC,**
Warsaw, IN (US)

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 213 days.

26,501 A 12/1859 Kendrick et al.
64,499 A 5/1867 Daubert
(Continued)

(21) Appl. No.: **14/275,548**

FOREIGN PATENT DOCUMENTS

(22) Filed: **May 12, 2014**

AU 4957264 3/1966
AU 440266 10/1967
(Continued)

(65) **Prior Publication Data**

US 2014/0330311 A1 Nov. 6, 2014

OTHER PUBLICATIONS

“JuggerKnot™ Soft Anchor: Arthroscopic and Mini-Open Rotator
Cuff Repair Using JuggerKnot™ Soft Anchor—2.9mm with
ALLthread™ Knotless Anchor Surgical Technique” brochure,
Biomet® Sports Medicine. (2013) 16 pages.

Related U.S. Application Data

(Continued)

(60) Division of application No. 13/412,127, filed on Mar.
5, 2012, now Pat. No. 8,721,684, which is a division
(Continued)

Primary Examiner — Alexander Orkin

(74) *Attorney, Agent, or Firm* — Schwegman Lundberg &
Woessner, P.A.

(51) **Int. Cl.**

A61B 17/04 (2006.01)
A61B 17/06 (2006.01)

(Continued)

(57) **ABSTRACT**

(52) **U.S. Cl.**

CPC **A61B 17/0401** (2013.01); **A61B 17/04**
(2013.01); **A61B 17/0469** (2013.01);

(Continued)

An assembly for coupling a first portion of an anatomy to a
second portion of the anatomy includes an anchor having an
anchor body and a first and second bores through the anchor
body. A first adjustable suture construct having a body
portion passes through the first bore of the anchor and
includes first and second adjustable loops slidable relative to
a passage portion defined in the body portion of the first
adjustable suture construct. A similar second adjustable
suture construct passes through the second bore of the
anchor.

(58) **Field of Classification Search**

CPC . A61B 17/04; A61B 17/0485; A61B 17/0487;
A61B 17/0401; A61B 2017/0417; A61B
2017/0496; A61B 2017/06185; A61F

20 Claims, 21 Drawing Sheets

