

5

a base wall,  
 a peripheral outer wall, and  
 an inner wall spaced from said outer wall and having an internal thread for securement to the container finish,  
 said outer wall having diametrically opposed circumferential gaps,  
 said inner wall extending axially in radial alignment with said gaps for circumferential abutment with the container lug,  
 said inner wall being flexible inwardly for clearing the lug and permitting removal of the closure from the container finish.

2. The closure set forth in claim 1 wherein said inner wall has diametrically opposed circumferentially spaced tabs that extend axially in radial alignment with said gaps in said outer wall.

3. The closure set forth in claim 2 wherein said gaps in said outer wall extend axially from said base wall to a free axial edge of said outer wall.

4. The closure set forth in claim 3 further comprising radial webs that connect said inner wall to said outer wall at said gaps in said outer wall.

5. The closure set forth in claim 3 wherein said closure further includes an annular lip extending axially from said base wall and spaced radially inwardly from said inner wall for sealing engagement with an inside diameter of a container finish.

6. The closure set forth in claim 3 wherein said outer wall has straight parallel circumferentially opposed edges that radially overlap circumferentially opposed straight parallel edges of said tabs at said gaps.

7. The closure set forth in claim 6 wherein said gaps each have a chordal dimension of about one-half to about three-quarters of an inch.

8. A child-resistant package that comprises:

a container having a finish with an external thread and at least one axial lug on a shoulder spaced from said thread, and

a closure of integrally molded plastic construction and comprising:

a base wall,  
 a peripheral outer wall, and  
 an inner wall spaced from said outer wall and having an internal thread for securement to the container finish,  
 said outer wall having diametrically opposed circumferential gaps,  
 said inner wall extending axially in radial alignment with said gaps for circumferential abutment with the container lug,

6

said inner wall being flexible inwardly for clearing the lug and permitting removal of the closure from the container finish.

9. The package set forth in claim 8 wherein said inner wall has diametrically opposed circumferentially spaced tabs that extend axially in radial alignment with said gaps in said outer wall.

10. The package set forth in claim 9 wherein said container has diametrically opposed lugs on said shoulder with clockwise oriented radially faces disposed for abutment with said tabs in an undetected position of said tabs.

11. The package set forth in claim 10 further comprising radial webs that connect said inner wall to said outer wall at said gaps in said outer wall.

12. The package set forth in claim 10 wherein said closure further includes an annular lip extending axially from said base wall and spaced radially inwardly from said inner wall for sealing engagement with an inside diameter of a container finish.

13. The package set forth in claim 10 wherein said lugs have counterclockwise oriented faces for camming said tabs radially inwardly as said closure is threaded onto said finish.

14. The package set forth in claim 13 wherein said lugs have radially outwardly oriented arcuate faces disposed radially inwardly of said outer wall for supporting said outer wall against radially inward movement.

15. The package set forth in claim 10 wherein said gaps in said outer wall extend axially from said base wall to a free axial edge of said outer wall.

16. The package set forth in claim 15 wherein said outer wall has straight parallel circumferentially opposed edges that radially overlap circumferentially opposed straight parallel edges of said tabs at said gaps.

17. The package set forth in claim 16 wherein said gaps each have a chordal dimension of about one-half to about three-quarters of an inch.

18. A method of making a child-resistant closure that comprises the steps of:

- (a) molding a closure of plastic construction comprising a base wall, a peripheral outer wall, and an inner wall spaced from said outer wall and having an internal thread,
- (b) forming diametrically opposed circumferential gaps in said outer wall, and
- (c) forming diametrically opposed flexible tabs that axially extend from said inner wall in radial alignment with said gaps.

\* \* \* \* \*