

190 may be configured to utilize output data **180** for generating real-time dynamic routing **196**.

Many applications of the output data **180** are contemplated. For example, filling in missing speed values **162** from collected GPS data **112** and estimating traffic link speed **182** for all links **116** at all time periods therefrom enables, as noted above dynamic, real-time routing **196** of all aggregated traffic in a network comprised of inter-connected road segments. Such dynamic routing **196** is useful for alleviating congestion on roadways and aiding traffic planners in real-time for improving work zone safety and efficiency in mass transit operations in response to current traffic speeds. Operational analytics **194** has applicability in congestion, mass transit, and work zone management, such analytics may also be useful in modeling real-time responses during disaster and emergency situations, such as for example traffic routing during tornado warnings in metropolitan areas. A complete link estimate **182** of traffic speed enables visualization **192** of traffic data that may be realized in a number of ways, such as in an animated map for distribution to media outlets or web applications, and may be specifically configured for display using a mobile device.

The systems and methods of the present invention may be implemented in many different computing environments **120**. For example, they may be implemented in conjunction with a special purpose computer, a programmed microprocessor or microcontroller and peripheral integrated circuit element(s), an ASIC or other integrated circuit, a digital signal processor, electronic or logic circuitry such as discrete element circuit, a programmable logic device or gate array such as a PLD, PLA, FPGA, PAL, and any comparable means. In general, any means of implementing the methodology illustrated herein can be used to implement the various aspects of the present invention. Exemplary hardware that can be used for the present invention includes computers, handheld devices, telephones (e.g., cellular, Internet enabled, digital, analog, hybrids, and others), and other such hardware. Some of these devices include processors (e.g., a single or multiple microprocessors), memory, nonvolatile storage, input devices, and output devices. Furthermore, alternative software implementations including, but not limited to, distributed processing, parallel processing, or virtual machine processing can also be configured to perform the methods described herein.

The systems and methods of the present invention may also be partially implemented in software that can be stored on a storage medium, executed on programmed general-purpose computer with the cooperation of a controller and memory, a special purpose computer, a microprocessor, or the like. In these instances, the systems and methods of this invention can be implemented as a program embedded on personal computer such as an applet, JAVA® or CGI script, as a resource residing on a server or computer workstation, as a routine embedded in a dedicated measurement system, system component, or the like. The system can also be implemented by physically incorporating the system and/or method into a software and/or hardware system.

Additionally, the data processing functions disclosed herein may be performed by one or more program instructions stored in or executed by such memory, and further may be performed the by one or more modules configured to carry out those program instructions. Modules are intended to refer to any known or later developed hardware, software, firmware, artificial intelligence, fuzzy logic, expert system or combination of hardware and software that is capable of performing the data processing functionality described herein.

The foregoing descriptions of embodiments of the present invention have been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Accordingly, many alterations, modifications and variations are possible in light of the above teachings, may be made by those having ordinary skill in the art without departing from the spirit and scope of the invention. It is therefore intended that the scope of the invention be limited not by this detailed description. For example, notwithstanding the fact that the elements of a claim are set forth below in a certain combination, it must be expressly understood that the invention includes other combinations of fewer, more or different elements, which are disclosed in above even when not initially claimed in such combinations.

The words used in this specification to describe the invention and its various embodiments are to be understood not only in the sense of their commonly defined meanings, but to include by special definition in this specification structure, material or acts beyond the scope of the commonly defined meanings. Thus if an element can be understood in the context of this specification as including more than one meaning, then its use in a claim must be understood as being generic to all possible meanings supported by the specification and by the word itself.

The definitions of the words or elements of the following claims are, therefore, defined in this specification to include not only the combination of elements which are literally set forth, but all equivalent structure, material or acts for performing substantially the same function in substantially the same way to obtain substantially the same result. In this sense it is therefore contemplated that an equivalent substitution of two or more elements may be made for any one of the elements in the claims below or that a single element may be substituted for two or more elements in a claim. Although elements may be described above as acting in certain combinations and even initially claimed as such, it is to be expressly understood that one or more elements from a claimed combination can in some cases be excised from the combination and that the claimed combination may be directed to a sub-combination or variation of a sub-combination.

Insubstantial changes from the claimed subject matter as viewed by a person with ordinary skill in the art, now known or later devised, are expressly contemplated as being equivalently within the scope of the claims. Therefore, obvious substitutions now or later known to one with ordinary skill in the art are defined to be within the scope of the defined elements.

The claims are thus to be understood to include what is specifically illustrated and described above, what is conceptually equivalent, what can be obviously substituted and also what essentially incorporates the essential idea of the invention.

The invention claimed is:

1. A method of determining real-time traffic speed over a plurality of links in a transportation network, comprising:
 - ingesting collected global positioning system (GPS) data from one or more sources and link data representing one or more links forming a transportation network;
 - processing the collected GPS data within a computing environment comprised of hardware and software components and a plurality of data processing functions executed by at least one processor and configured to fill in speed values missing from GPS data, by:
 - initiating a model of rescaled speed estimation by mapping the collected GPS data to the to one or more links comprising a transportation network, identifying a set