



US009409324B2

(12) **United States Patent**
Haar

(10) **Patent No.:** **US 9,409,324 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **METHOD AND DEVICE FOR APPLYING A SEALING COMPOUND TO A SURFACE**
(75) Inventor: **Thomas Haar**, Halstenbek (DE)
(73) Assignee: **SAETA GMBH & CO. KG**, Wedel (DE)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 654 days.

(58) **Field of Classification Search**
None
See application file for complete search history.

(21) Appl. No.: **13/391,969**
(22) PCT Filed: **Aug. 27, 2010**
(86) PCT No.: **PCT/EP2010/005276**
§ 371 (c)(1),
(2), (4) Date: **Mar. 20, 2012**

(56) **References Cited**
U.S. PATENT DOCUMENTS
4,388,058 A 6/1983 Kubo
2003/0131927 A1* 7/2003 Hatcher et al. 156/230
2009/0127744 A1 5/2009 Hanot

(87) PCT Pub. No.: **WO2011/023399**
PCT Pub. Date: **Mar. 3, 2011**
(65) **Prior Publication Data**
US 2012/0171381 A1 Jul. 5, 2012

FOREIGN PATENT DOCUMENTS
EP 0 462 513 A1 12/1991
EP 0 499 108 A1 8/1992
EP 1 527 864 A1 5/2005
EP 1527864 A1 * 5/2005 B29C 31/04
JP 6-312762 11/1994
JP 2004042471 A * 2/2004 B29C 43/18
* cited by examiner

(30) **Foreign Application Priority Data**
Aug. 28, 2009 (DE) 10 2009 040 802

Primary Examiner — Lisha Jiang
(74) *Attorney, Agent, or Firm* — Vidas, Arrett & Steinkraus, P.A.

(51) **Int. Cl.**
B29C 31/00 (2006.01)
B29C 43/18 (2006.01)
B05D 1/26 (2006.01)
B05C 1/02 (2006.01)
B05D 1/28 (2006.01)
B05D 3/12 (2006.01)
B29C 31/04 (2006.01)
B29C 43/34 (2006.01)
B29C 43/36 (2006.01)
B29L 31/56 (2006.01)
(52) **U.S. Cl.**
CPC **B29C 43/18** (2013.01); **B29C 31/048** (2013.01); **B29C 43/34** (2013.01); **B29C 2043/3433** (2013.01); **B29C 2043/3626** (2013.01); **B29L 2031/565** (2013.01)

(57) **ABSTRACT**
A device for applying a sealing compound into a closure cap for containers comprising:
an outer stamp (18) and a concentric inner stamp (14), the stamps being movable with respect to each other, an annular gap (26) between the stamps (14, 18), which is open towards the outside or the inside and of which at least one section is variable between an initial gap width and a gap width zero in the movement direction of the stamps in an axial relative movement of the stamps (14, 18),
a feeding system for plasticized sealing compound within a stamp, which is connected to the annular gap (26),
a mechanism that prevent any reflux of the melt from the annular gap, and
adjustment mechanism for at least one of the stamps for changing the gap width of the annular gap.

10 Claims, 3 Drawing Sheets

