United States Patent [19]

Karimi et al.

[11] **Patent Number: 5,061,424**

[45] **Date of Patent: Oct. 29, 1991**

[54] **METHOD FOR APPLYING A LUBRICIOUS COATING TO AN ARTICLE**

[75] Inventors: **Houshang Karimi**, Centerville; **Mutlu Karakelle**, Spring Valley; **Robert A. Taller**, Centerville, all of Ohio

[73] Assignee: **Becton, Dickinson and Company**, Franklin Lakes, N.J.

[21] Appl. No.: **643,639**

[22] Filed: **Jan. 22, 1991**

[51] **Int. Cl.**[5] **B29C 47/06**

[52] **U.S. Cl.** **264/171**; 264/130; 264/173; 264/300; 264/331.19; 264/209.1

[58] **Field of Search** 264/171, 173, 300, 130, 264/514, 150, 331.19, 209.1

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,062,834	12/1977	Gilding et al. .	
4,100,309	7/1978	Micklus et al. .	
4,211,741	7/1980	Ostoich	264/173
4,299,256	11/1981	Bacehowski et al.	264/173
4,373,009	2/1983	Winn .	
4,485,062	11/1984	Dawes et al.	264/171
4,551,292	11/1985	Fletcher et al.	264/173
4,642,267	2/1987	Creasy et al. .	
4,720,521	1/1988	Spielvogel et al. .	
4,767,414	8/1988	Williams et al. .	
4,880,592	11/1989	Martini et al.	264/514
4,904,431	2/1990	O'Maleki	264/173
4,952,359	8/1990	Wells	264/173
4,963,306	10/1990	Weldon	264/150

OTHER PUBLICATIONS

Nagoaka et al., *Biomaterials*, 419, (1990).

Petrothene® Polyolefins—A Processing Guide, Fifth Edition, 1986, p. 73 et seq., USI Chemicals, Division of National Distillers and Chemical Corp.

Michaeli, *Extrusion Dies*, p. 210, et seq., Hanser Publishers, New York, New York, 1984.

Handbook of Water Soluble Gums and Resins, R. L. Davidson, Ed., McGraw-Hill 1980, pp. 21.1-21.2.

Primary Examiner—Jeffery Thurlow

Attorney, Agent, or Firm—Richard E. Brown

[57] **ABSTRACT**

A composition which includes polyvinylpyrrolidone and a polyurethane is melt processed to give a shaped article. The melt processing may be a coextrusion with a substrate polymer to give a shaped article having the composition coated on the surface thereof. The article surface is lubricious when contacted with water.

16 Claims, No Drawings