

13

said tip exerts on said underside of said forearm of said golfer when said angle β is substantially equal to said predetermined value.

3. The device of claim 1 wherein said curved surface has an arc radius ≈ 0.400 inches.

4. The device claim 1 wherein the length of said arc radius varies along said curved surface between substantially 0.425 inches and 0.395 inches.

5. The device of claim 1 wherein said curved surface is a partial surface of a cylinder or a cone, said partial surface subtending a radial arc angle of less than 180 degrees.

6. The device of claim 5 wherein said partial surface subtends a radial arc angle of between substantially 100 degrees and 120 degrees.

7. The device of claim 1 wherein said interface is configured in such a way that the device will not remain in contact with said particular portion of a golf club unless held there by means external to the device itself.

8. The device of claim 1 wherein said interface includes means for attaching the device to a golf club in such a way that the device will remain attached to the golf club when the golf club is not being held itself.

9. A device that provides a particular human-perceptible stimulus to a golfer when the golfer is holding a grip portion of a golf club with both of the golfer's thumbs extending along a shaft of the golf club, the device being configured to provide said particular human-perceptible stimulus only when a shaft-to-forearm angle β between a centerline of a forearm of the golfer and a shaft of the golf club is at a predetermined value substantially between 145 degrees and 160 degrees,

wherein said device has a U-shape comprising first and second arms and a base portion,

the first arm comprising an interface and an inter-finger portion, said interface and said inter-finger portion being configured in such a way that the interface can be held in contact with a grip of a golf club by a hand of the golfer with the inter-finger portion extending away from the grip of the golf club between a pair of adjacent fingers of the golfer, the second arm terminating in a tip and the base portion interconnecting the first and second arms, the first and second arms and the base portion being proportioned such that said tip provides a tactile stimulus at the underside of a forearm of the golfer when said shaft-to-forearm angle β is at said predetermined value.

10. The device of claim 9 wherein said interface has a curved surface with a varying arc radius.

11. A golf training device comprising an interface having a curved surface that is a partial surface of a cylinder or a cone,

an inter-finger portion connected to said interface having first and second ends, wherein the first end is connected at a convex side of said interface, and wherein a central axis of the inter-finger portion intersects both said interface and the axis of said cylinder or cone,

a tactile feedback member having a fixed end and a free end, and

a connecting member that connects the second end of the inter-finger portion to the fixed end of the tactile feedback member,

the tactile feedback member being such that its free end deflects relative to the training device as a whole in response to a lateral force applied to said free end.

12. The golf training device of claim 11 wherein a distance between a tip of the free end and the connecting member is adjustable.

14

13. The golf training device of claim 11 wherein the device is configured in such a way that there is an angle α between a first line and a second line,

wherein said angle α has a value between substantially 11 degrees and 21 degrees,

wherein the first line is a shortest line between a) a point where said arc radius centerline axis intersects with a plane that contains said inter-finger member and b) said tactile feedback member,

and wherein the second line is said arc radius centerline axis.

14. The golf training device of claim 11 wherein the device is configured in such a way that there is an angle Ω between a first line and a second line,

wherein said angle Ω has a value between substantially 35 degrees and 45 degrees,

wherein the first line is a shortest line between a) a point where said arc radius centerline axis intersects with a plane that contains said inter-finger member and b) said tactile feedback member,

and wherein the second line is a line extending between said point and a terminating point of said free end.

15. A method performed by a golfer holding a golf club, the method comprising positioning in contact with the golf club a device that provides a particular human-perceptible stimulus to the golfer only when both a) the golfer is holding a grip portion of the golf club with both of the golfer's thumbs extending along a shaft of the golf club, and b) a shaft-to-forearm angle β between a centerline of a forearm of the golfer and a shaft of the golf club is substantially between 145 degrees and 160 degrees,

wherein the device includes a forearm-contacting tip,

wherein said particular human-perceptible stimulus is a perceptible amount of pressure exerted on a forearm of the golfer by the forearm-contacting tip, wherein the device is configured in such a way that the forearm-contacting tip exerts pressure on a forearm of the golfer only when said shaft-to-forearm angle β is at at least said predetermined value, and wherein the device is further configured in such a way that, when said angle β is greater than said predetermined value, said tip exerts a higher amount of pressure on said underside of said forearm than said perceptible amount of pressure that said tip exerts on said underside of said forearm of said golfer when said angle β is substantially equal to said predetermined value.

16. A device that provides a particular human-perceptible stimulus to a golfer when the golfer is holding a grip portion of a golf club with both of the golfer's thumbs extending along a shaft of the golf club, the device being configured to provide said particular human-perceptible stimulus only when a shaft-to-forearm angle β between a centerline of a forearm of the golfer and a shaft of the golf club is at a predetermined value substantially between 145 degrees and 160 degrees,

wherein said device has an interface that can be positioned in contact with a particular portion of a golf club,

wherein said device is configured such that said stimulus is provided at a time when said interface is in contact with said particular portion of the golf club,

wherein said particular portion of the golf club is the grip of the golf club,

and wherein said device includes an inter-finger element that is attached to said interface and that is so configured that the inter-finger element can extend between adja-