US009409627B2

(12) **United States Patent**
Fulop et al.

(10) **Patent No.: US 9,409,627 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **COLLAPSIBLE WATERCRAFT ASSEMBLY**

(71) Applicants: **Joseph Webb Fulop**, Mission (CA); **Anthony Fulop**, Creston (CA)

(72) Inventors: **Joseph Webb Fulop**, Mission (CA); **Anthony Fulop**, Creston (CA)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/817,230**

(22) Filed: **Aug. 4, 2015**

(65) **Prior Publication Data**

US 2016/0039498 A1 Feb. 11, 2016

Related U.S. Application Data

(60) Provisional application No. 62/035,835, filed on Aug. 11, 2014.

(51) **Int. Cl.**
B63B 7/02 (2006.01)
B63B 1/12 (2006.01)

(52) **U.S. Cl.**
CPC ***B63B 7/02*** (2013.01); *B63B 2001/123* (2013.01); *B63B 2241/26* (2013.01)

(58) **Field of Classification Search**
CPC B63B 7/00; B63B 7/02; B63B 7/04; B63B 1/00; B63B 1/12; B63B 1/121
USPC 114/61.22, 352, 353, 354
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,883,909 A * 5/1975 Fisher B63B 7/04 114/352
4,828,517 A 5/1989 Van Liefland
4,919,632 A * 4/1990 Smith B63B 1/121 114/352
5,074,233 A 12/1991 Weed
5,086,721 A 2/1992 Burkard
5,088,944 A 2/1992 Kats
5,374,206 A 12/1994 Gregory
5,619,943 A 4/1997 Kieronski
5,651,706 A 7/1997 Kasper
5,692,450 A 12/1997 Alter et al.
6,311,632 B1 11/2001 Noel, Jr.
6,345,582 B1 2/2002 Dudink
6,508,194 B2 1/2003 Myers
6,988,456 B1 1/2006 Schooler
7,096,817 B1 8/2006 Scadden
7,354,326 B2 4/2008 Lukens
7,461,607 B2 12/2008 Reilly et al.
7,587,986 B2 9/2009 Neidert et al.
8,656,856 B1 2/2014 Morrow
(Continued)

FOREIGN PATENT DOCUMENTS

DE 4341781 A1 6/1995
WO 03016131 A1 2/2003

Primary Examiner — Lars A Olson

(57) **ABSTRACT**

A collapsible watercraft assembly can include a first pontoon half, a second pontoon half, and a frame member. Each pontoon half can have a top surface, a bottom surface, and at least one post. The first pontoon half and the second pontoon half can be positionable with respect to one another in an operating configuration and a stowed configuration. The operating configuration can be defined when the sterns of the pontoon halves confront one another and the stowed configuration can be defined when the top surfaces of the pontoon halves confront one another. The frame member can be concurrently engageable with the posts to fix the pontoon halves together in the operating configuration. The posts can be interconnected with one another when the first pontoon half and the second pontoon half are in the stowed configuration.

20 Claims, 6 Drawing Sheets