US009411427B2

(12) **United States Patent**
Kobori

(10) **Patent No.: US 9,411,427 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **ENTRY DEVICE AND PAPER SHEETS HANDLING DEVICE**

(71) Applicant: **Oki Electric Industry Co., Ltd.**, Tokyo (JP)

(72) Inventor: **Hideki Kobori**, Tokyo (JP)

(73) Assignee: **OKI ELECTRIC INDUSTRY CO., LTD.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/407,803**

(22) PCT Filed: **May 28, 2013**

(86) PCT No.: **PCT/JP2013/064781**

§ 371 (c)(1),
(2) Date: **Dec. 12, 2014**

(87) PCT Pub. No.: **WO2014/010321**

PCT Pub. Date: **Jan. 16, 2014**

(65) **Prior Publication Data**

US 2015/0185863 A1 Jul. 2, 2015

(30) **Foreign Application Priority Data**

Jul. 9, 2012 (JP) 2012-153411

(51) **Int. Cl.**

G06F 21/83	(2013.01)
G06F 3/023	(2006.01)
G06F 21/70	(2013.01)
G06F 21/82	(2013.01)
G06F 21/00	(2013.01)
G06F 3/02	(2006.01)
G06F 21/31	(2013.01)
G06Q 20/10	(2012.01)
G07F 19/00	(2006.01)
G07F 7/10	(2006.01)

(52) **U.S. Cl.**

CPC ***G06F 3/023*** (2013.01); ***G06F 3/0219*** (2013.01); ***G06F 21/00*** (2013.01); ***G06F 21/31*** (2013.01); ***G06F 21/70*** (2013.01); ***G06F 21/82*** (2013.01); ***G06F 21/83*** (2013.01); ***G06Q 20/1085*** (2013.01); ***G07F 7/1033*** (2013.01); ***G07F 19/20*** (2013.01); ***G07F 19/201*** (2013.01)

(58) **Field of Classification Search**

CPC G06F 21/00; G06F 21/70; G06F 21/82; G06F 21/83

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,362,973	B1 *	4/2008	Dickson	G06F 21/83 340/540
7,899,325	B2 *	3/2011	Dickson	G06F 21/83 398/40
8,015,593	B2 *	9/2011	Dickson	G06F 21/83 340/540
8,750,705	B2 *	6/2014	Dickson	G06F 21/83 340/540
2008/0072331	A1 *	3/2008	Dickson	G06F 21/83 726/26
2012/0212319	A1 *	8/2012	Ling	G06F 1/3203 340/3.1

FOREIGN PATENT DOCUMENTS

JP	H03-104223	U	10/1991
JP	H10-40439	A	2/1998
JP	2011-100383	A	5/2011

OTHER PUBLICATIONS

Keaton Mowery et al., "Heat of the Moment: Characterizing the Efficacy of Thermal Camera-Based Attacks", Proceeding WOOT'11, Proceedings of the 5th USENIX conference on Offensive technologies, 2011, pp. 1-8.

* cited by examiner

Primary Examiner — Andrew Bee

(74) *Attorney, Agent, or Firm* — Rabin & Berdo, P.C.

(57) **ABSTRACT**

An entry device is provided with a plural number of operation keys and a temperature changing unit. The operation keys can be operated by pressing by a fingertip of a hand touching respective operation surfaces thereof, and are used for entry of an authentication character string. When the authentication character string is to be entered, the temperature changing unit changes temperatures of the operation surfaces of the plural operation keys to be substantially equal.

15 Claims, 23 Drawing Sheets