

- [54] **DOUBLE LUMEN CANNULA**
- [75] Inventors: **James L. Sorenson; Karl A. Pannier, Jr.,** both of Salt Lake City; **Gordon S. Reynolds,** Bountiful, all of Utah
- [73] Assignee: **Sorenson Research Co., Inc.,** Salt Lake City, Utah
- [21] Appl. No.: **769,591**
- [22] Filed: **Feb. 17, 1977**
- [51] Int. Cl.² **A61M 5/00; A61M 25/00**
- [52] U.S. Cl. **128/214.4; 128/348; 128/DIG. 16**
- [58] Field of Search **128/214 R, 214.4, 221, 128/DIG. 16, 347, 348**

[56] **References Cited**
U.S. PATENT DOCUMENTS

3,220,411	11/1965	Czorny	128/214.4
3,610,226	10/1971	Albisser	128/214 R
4,000,739	1/1977	Stevens	128/214.4
4,014,333	3/1977	McIntyre	128/214.4 X
4,022,219	5/1977	Basta	128/351

4,054,136 10/1977 Zeppelin 128/214.4

OTHER PUBLICATIONS

Kruger, IBM Tech. Disclosure Bulletin, vol. 19, No. 4, Sep. 1976, pp. 1174-1175.

Primary Examiner—Dalton L. Truluck
Attorney, Agent, or Firm—H. Ross Workman; J. Winslow Young

[57] **ABSTRACT**

A double lumen cannula mounted upon a hub and constructed to penetrate the human vascular system, the cannula assembly having an interior cannula and an exterior cannula spaced from the interior cannula. A bushing is normally situated in the space between the interior and exterior cannula which bushing facilitates venipuncture without damaging the tissue. After venipuncture, the bushing is removable from the space between the interior and exterior cannulae by withdrawing the bushing from the cannulae through the hub.

8 Claims, 4 Drawing Figures

