US009410529B2

(12) **United States Patent**
Grove-Nielsen

(10) **Patent No.: US 9,410,529 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **ROTOR BLADE FOR A WIND TURBINE**

(71) Applicant: **SIEMENS AKTIENGESELLSCHAFT**, München (DE)

(72) Inventor: **Erik Grove-Nielsen**, Roslev (DK)

(73) Assignee: **SIEMENS AKTIENGESELLSCHAFT**, München (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/816,542**

(22) Filed: **Aug. 3, 2015**

(65) **Prior Publication Data**

US 2015/0337797 A1 Nov. 26, 2015

Related U.S. Application Data

(63) Continuation of application No. 13/490,655, filed on Jun. 7, 2012, now abandoned.

(30) **Foreign Application Priority Data**

Jun. 10, 2011 (EP) 11169517

(51) **Int. Cl.**
F03D 1/00 (2006.01)
F03D 1/06 (2006.01)

(52) **U.S. Cl.**
CPC ***F03D 1/001*** (2013.01); ***F03D 1/065*** (2013.01); ***F03D 1/0658*** (2013.01); ***F03D 1/0675*** (2013.01); ***F03D 1/0691*** (2013.01); *F05B 2240/40* (2013.01); *F05B 2240/80* (2013.01); *F05B 2240/90* (2013.01); *Y02E 10/721* (2013.01); *Y02E 10/728* (2013.01)

(58) **Field of Classification Search**
CPC F03D 1/0633; F03D 1/0641; F03D 1/065; F03D 1/0675; F03D 1/0683; F03D 1/0691; F03D 1/0658
USPC ..... 416/204 R, 204 A, 205, 207–209, 214 R, 416/214 A, 219 A, 220 A, 239, 244 R, 244 A, 416/248, 174, 241 A, 229 R, 230, 226
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,915,590	A	4/1990	Eckland et al.	
2005/0106029	A1*	5/2005	Kildegaard	B29C 70/525 416/229 R
2010/0043318	A1	2/2010	Ambrecht et al.	
2011/0020131	A1*	1/2011	Petersen	B29D 99/0025 416/226
2011/0044817	A1	2/2011	Bendel et al.	
2012/0045343	A1	2/2012	Hancock et al.	

FOREIGN PATENT DOCUMENTS

DE	10011464	C1	8/2001
EP	1959129	A2	8/2008
EP	1975405	A2	10/2008

(Continued)

Primary Examiner — Christopher Verdier

(57) **ABSTRACT**

A rotor blade for a wind turbine has an elongate blade base body with a plurality of connecting elements. Each connecting element comprises at least one axially extending connecting portion adapted to be connected with corresponding connecting portions of a rotor hub of the wind turbine. The connecting elements are connected in a circumferential direction so as to build a closed ring-shape.

12 Claims, 3 Drawing Sheets