



US008727129B2

(12) **United States Patent**
Rose et al.

(10) **Patent No.:** **US 8,727,129 B2**
(45) **Date of Patent:** **May 20, 2014**

(54) **MICROFLUIDIC ULTRASONIC PARTICLE SEPARATORS WITH ENGINEERED NODE LOCATIONS AND GEOMETRIES**

(75) Inventors: **Klint A. Rose**, Alviso, CA (US); **Karl A. Fisher**, Brentwood, CA (US); **Douglas A. Wajda**, Urbana, IL (US); **Raymond P. Mariella, Jr.**, Danville, CA (US); **Christopher Bailey**, Pleasanton, CA (US); **Dietrich Dehlinger**, Dublin, CA (US); **Maxim Shusteff**, Oakland, CA (US); **Byoungsok Jung**, Palo Alto, CA (US); **Kevin D. Ness**, Pleasanton, CA (US)

(73) Assignee: **Lawrence Livermore National Security, LLC.**, Livermore, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/571,640**

(22) Filed: **Aug. 10, 2012**

(65) **Prior Publication Data**
US 2013/0043170 A1 Feb. 21, 2013

Related U.S. Application Data

(60) Provisional application No. 61/524,020, filed on Aug. 16, 2011.

(51) **Int. Cl.**
B03B 5/00 (2006.01)

(52) **U.S. Cl.**
USPC **209/455; 209/457; 209/458**

(58) **Field of Classification Search**
USPC 209/454, 455, 457, 458
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

6,332,541 B1 * 12/2001 Coakley et al. 209/18
7,674,630 B2 * 3/2010 Siverson 436/177
2010/0126922 A1 * 5/2010 Takahashi et al. 210/201

OTHER PUBLICATIONS

Karl A. Fisher and Robin Miles, "Modeling the acoustic radiation force in microfluidic chambers (L)," J. Acoust. Soc. Am. 123 (4): 1862-1865 (2008).
A. Haake and J. Dual, "Micro-manipulation of small particles by node position control of an ultrasonic standing wave," Ultrasonics, 40 : 317-322 (2002).
Hawkes et al., "Filtration of bacteria and yeast by ultrasound-enhanced sedimentation," J. of Applied Microbiology, 82: 39-47 (1997).
Glynn-Jones et al., "Multi-modal particle manipulator to enhance bead-based bioassays," Ultrasonics, 50: 235-239 (2010).
Jung et al., "Acoustic Particle Filter with Adjustable Effective Pore Size for Automated Sample Preparation," Anal. Chem., 80: 8447-8452 (2008).
Laurell et al., "Chip integrated strategies for acoustic separation and manipulation of cells and particles," Chem. Soc. Rev., 36: 492-506 (2007).

* cited by examiner

Primary Examiner — David H Bollinger
(74) *Attorney, Agent, or Firm* — Eddie E. Scott

(57) **ABSTRACT**

An ultrasonic microfluidic system includes a separation channel for conveying a sample fluid containing small particles and large particles, flowing substantially parallel, adjacent to a recovery fluid, with which it is in contact. An acoustic transducer produces an ultrasound standing wave, that generates a pressure field having at least one node of minimum pressure amplitude. An acoustic extension structure is located proximate to said separation channel for positioning said acoustic node off center in said acoustic area and concentrating the large particles in said recovery fluid stream.

4 Claims, 5 Drawing Sheets

