



US009408430B2

(12) **United States Patent**
Guay et al.

(10) **Patent No.:** **US 9,408,430 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **PROTECTIVE HELMET AND SCREEN**

(71) Applicant: **MSA Gallet**, Chatillon sur Chalaronne (FR)

(72) Inventors: **Louis Guay**, Chatillon sur Chalaronne (FR); **Pascal Michel**, Dompierre sur Chalaronne (FR)

(73) Assignee: **MSA Production France**, Chatillon sur Chalaronne (FR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 84 days.

(21) Appl. No.: **14/384,503**

(22) PCT Filed: **Mar. 11, 2013**

(86) PCT No.: **PCT/EP2013/054810**
§ 371 (c)(1),
(2) Date: **Sep. 11, 2014**

(87) PCT Pub. No.: **WO2013/135599**
PCT Pub. Date: **Sep. 19, 2013**

(65) **Prior Publication Data**
US 2015/0040299 A1 Feb. 12, 2015

(30) **Foreign Application Priority Data**
Mar. 15, 2012 (FR) 12 52315

(51) **Int. Cl.**
A42B 3/22 (2006.01)
A42B 3/04 (2006.01)

(52) **U.S. Cl.**
CPC . **A42B 3/221** (2013.01); **A42B 3/04** (2013.01);
A42B 3/222 (2013.01)

(58) **Field of Classification Search**

CPC A42B 3/04; A42B 3/222; A42B 3/228
USPC 2/422, 424, 6.3, 6.4, 6.5, 6.7, 15
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,748,696 A * 6/1988 Fohl A42B 3/223
2/10

5,012,528 A 5/1991 Pernicka
(Continued)

FOREIGN PATENT DOCUMENTS

DE 2640996 A1 3/1978
EP 2292112 A1 3/2011

(Continued)

Primary Examiner — Tejash Patel

(74) *Attorney, Agent, or Firm* — The Webb Law Firm

(57) **ABSTRACT**

A screen for a safety helmet, including a principal part having at least one wing with at least one linkage piece mounted thereto, where the linkage piece includes: a first arrangement for connecting the screen to the shell and configured to facilitate pivoting of the at least one linkage piece relative to the shell, such that the screen is moveable between a low position, in which the screen is substantially covering the face opening, and a high position, in which the face opening is substantially clear; and a second arrangement for connecting to the at least one wing and configured to facilitate the pivoting of the principal part relative to the at least one linkage piece; wherein the principal part is moveable relative to the at least one linkage piece between a position substantially away from and a position substantially close to the face opening.

33 Claims, 7 Drawing Sheets

