



US007964230B2

(12) **United States Patent**
Kirschner et al.

(10) **Patent No.:** **US 7,964,230 B2**
(45) **Date of Patent:** **Jun. 21, 2011**

(54) **METHOD OF SEALING A POD FOR DISPERSIBLE MATERIALS**

(75) Inventors: **Jonathan Kirschner**, Powder Springs, GA (US); **Carter Crittenden Bennett**, Lilburn, GA (US)

(73) Assignee: **The Coca-Cola Company**, Atlanta, GA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1056 days.

(21) Appl. No.: **11/754,690**

(22) Filed: **May 29, 2007**

(65) **Prior Publication Data**

US 2008/0028946 A1 Feb. 7, 2008

Related U.S. Application Data

(63) Continuation-in-part of application No. 11/462,444, filed on Aug. 4, 2006.

(51) **Int. Cl.**
A47J 31/00 (2006.01)

(52) **U.S. Cl.** **426/433; 426/435; 426/77; 426/78**

(58) **Field of Classification Search** **426/433, 426/435, 77, 78; 99/287**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,951,357 A 3/1934 Hall
2,162,272 A * 6/1939 Patterson 426/77
2,292,101 A * 8/1942 Brown 426/77
2,743,664 A 5/1956 Dale

2,778,739 A 1/1957 Rodth
2,968,560 A 1/1961 Goros
3,151,418 A 10/1964 Powell et al.
3,275,448 A 9/1966 Sommer
3,428,460 A 2/1969 Ely
3,589,272 A 6/1971 Bouladon
3,713,842 A 1/1973 Lubsen et al.
3,812,273 A 5/1974 Schmidt
3,823,656 A 7/1974 Vekekn
3,888,999 A 6/1975 Jones et al.
3,952,641 A 4/1976 Vitous
4,081,560 A 3/1978 Ishigaki
4,107,339 A 8/1978 Shrimpton
4,158,330 A 6/1979 Vitous
4,254,694 A 3/1981 Illy
4,429,623 A 2/1984 Illy
4,471,689 A 9/1984 Piana
4,581,239 A 4/1986 Woolman et al.
4,644,855 A 2/1987 Woolman et al.

(Continued)

FOREIGN PATENT DOCUMENTS

BE 701863 1/1968

(Continued)

OTHER PUBLICATIONS

Brasilia S.p.A., PDM100 Spare Parts Catalog, Jan. 25, 2007, 35 pgs., Rev. No. 12, Retorbido, Italy.

Primary Examiner — Anthony Weier

(74) *Attorney, Agent, or Firm* — Sutherland Asbill & Brennan LLP

(57) **ABSTRACT**

A pod for mixing an amount of a dispersible material with water. The pod may include a pod body having a lower aperture and a poppet positioned within the aperture. The poppet may be sized so as to seal the lower aperture until a predetermined pressure is reached within the pod body.

8 Claims, 6 Drawing Sheets

