US009410432B2

(12) **United States Patent**
Matsumoto et al.

(10) **Patent No.: US 9,410,432 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **TURBINE**

(71) Applicant: **MITSUBISHI HEAVY INDUSTRIES, LTD.**, Tokyo (JP)

(72) Inventors: **Kazuyuki Matsumoto**, Tokyo (JP); **Yoshihiro Kuwamura**, Tokyo (JP); **Hiroharu Oyama**, Tokyo (JP); **Yoshinori Tanaka**, Tokyo (JP)

(73) Assignee: **Mitsubishi Hitachi Power Systems, Ltd.**, Kanagawa (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 778 days.

(21) Appl. No.: **13/753,910**

(22) Filed: **Jan. 30, 2013**

(65) **Prior Publication Data**

US 2013/0251534 A1 Sep. 26, 2013

(30) **Foreign Application Priority Data**

Mar. 23, 2012 (JP) 2012-067893

(51) **Int. Cl.**
F01D 5/12 (2006.01)
F01D 5/14 (2006.01)
F01D 11/10 (2006.01)

(52) **U.S. Cl.**
CPC ***F01D 5/12*** (2013.01); ***F01D 5/147*** (2013.01); ***F01D 11/10*** (2013.01); *F05D 2240/307* (2013.01); *F05D 2250/28* (2013.01)

(58) **Field of Classification Search**
CPC F01D 11/02; F01D 11/00; F01D 5/20; F01D 5/225
USPC 415/173.1, 173.5, 173.6, 174.5
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,971,882 B1 * 7/2011 Liang F01D 11/02 277/418
2009/0072487 A1 3/2009 Chougule et al.

FOREIGN PATENT DOCUMENTS

CN	2725533 Y	9/2005	
DE	2462465 A1 *	4/1977	..... F01D 11/02
JP	2002-228014	8/2002	
JP	2006-291967	10/2006	
JP	2008-223660	9/2008	

(Continued)

OTHER PUBLICATIONS

International Search Report mailed Apr. 16, 2013 in International (PCT) Application No. PCT/JP2013/052341 with English translation.

(Continued)

Primary Examiner — Nathaniel Wiehe
Assistant Examiner — Cameron Corday
(74) *Attorney, Agent, or Firm* — Wenderoth, Lind & Ponack, L.L.P.

(57) **ABSTRACT**

A plurality of stepped parts which have step surfaces facing an upstream side in a rotating axial direction of a structural member are provided in a tip portion of a blade, and seal fins which extend toward a circumference surface of each of the stepped parts and form small clearances between the seal fin and the circumference surface corresponding to the each of the stepped parts is provided in the structural member. Also, lengths from the small clearance to the step surface on the upstream side along the rotating axial direction of the structural member are set such that one of the stepped parts on the downstream side is smaller than the other one of the stepped parts on the upstream side.

6 Claims, 7 Drawing Sheets