



US009409635B2

(12) **United States Patent**  
**Leeuwenburgh**

(10) **Patent No.:** **US 9,409,635 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **TOW BAR HOLDER**

(71) Applicant: **Peter Leeuwenburgh**, BA Herwijnen (NL)

(72) Inventor: **Peter Leeuwenburgh**, BA Herwijnen (NL)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/410,802**

(22) PCT Filed: **Jun. 25, 2013**

(86) PCT No.: **PCT/EP2013/063294**  
§ 371 (c)(1),  
(2) Date: **Dec. 23, 2014**

(87) PCT Pub. No.: **WO2014/001343**  
PCT Pub. Date: **Jan. 3, 2014**

(65) **Prior Publication Data**  
US 2015/0144048 A1 May 28, 2015

(30) **Foreign Application Priority Data**  
Jun. 28, 2012 (DE) ..... 10 2012 211 165

(51) **Int. Cl.**  
**B63B 21/04** (2006.01)  
**B63B 35/81** (2006.01)  
**B63B 7/08** (2006.01)  
**B63H 20/02** (2006.01)  
**B63H 20/06** (2006.01)  
(52) **U.S. Cl.**  
CPC ..... **B63B 35/816** (2013.01); **B63B 7/087** (2013.01); **B63H 20/02** (2013.01); **B63H 20/06** (2013.01)

(58) **Field of Classification Search**  
CPC ..... B63B 35/816  
USPC ..... 114/253  
See application file for complete search history.

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
2,907,295 A 10/1959 Delaney  
2,920,598 A \* 1/1960 Nielsen ..... B63B 35/816  
114/253  
7,798,087 B2 \* 9/2010 Leeuwenburgh ..... B63B 35/815  
114/253

**FOREIGN PATENT DOCUMENTS**  
EP 1993904 B1 4/2012  
WO 2007097620 A1 8/2007

**OTHER PUBLICATIONS**  
International Search Report dated Sep. 20, 2013 for PCT application No. PCT/EP2013/063294.

(Continued)  
*Primary Examiner* — Stephen Avila  
(74) *Attorney, Agent, or Firm* — Ohlandt, Greeley, Ruggiero & Perle, LLP

(57) **ABSTRACT**  
A tow bar holder for securing a tow bar to a boat having an outboard engine has two separate securing elements secured to the stern of the boat. The securing elements each have a fixing element for securing to an engine plate, and a receiving element. The feet of the tow bar can be plugged into a receiving space of the receiving element. In this case, the internal dimensions of the receiving space are larger than the external dimensions of the feet of the tow bar, such that the tow bar is tiltable and/or is fixable in various positions in the receiving space.

**17 Claims, 7 Drawing Sheets**

