



US005674435A

United States Patent [19]

[11] Patent Number: 5,674,435

Blake

[45] Date of Patent: Oct. 7, 1997

[54] FABRICATION OF AN INTRAOCULAR LENS

[75] Inventor: Larry W. Blake, Irvine, Calif.

[73] Assignee: Pharmacia Iovision, Inc., Irvine, Calif.

[21] Appl. No.: 464,104

[22] Filed: Jun. 5, 1995

Related U.S. Application Data

[62] Division of Ser. No. 290,236, Aug. 15, 1994, abandoned, which is a continuation of Ser. No. 900,053, Jul. 27, 1992, which is a division of Ser. No. 705,771, May 28, 1991, Pat. No. 5,185,107, which is a division of Ser. No. 262,985, Oct. 26, 1988, Pat. No. 5,104,590.

[51] Int. Cl.⁶ B29D 11/00

[52] U.S. Cl. 264/2.7; 264/1.7; 264/161

[58] Field of Search 264/1.7, 1.8, 2.5, 264/2.7, 2.6, 161; 425/810; 457/42, 43

[56] References Cited

U.S. PATENT DOCUMENTS

385,905 7/1888 Cannon .
2,823,417 2/1958 Pasini et al. .
3,030,746 4/1962 Firestine et al. .

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

1103399 11/1955 France .
2556665 6/1977 Germany .
2717706 10/1978 Germany .
2725219 12/1978 Germany .
371898 11/1991 Japan .
WO9306967 4/1993 WIPO .

OTHER PUBLICATIONS

Grant & Hackh's Chemical Dictionary, 5th Edition, 1987, p. 265.

Waters, Tom, "3-D Comes Home," *Discover*, May 1988, pp. 30-32.

"Early Trials Show No Blurring of Vision with Multifocal IOL," *Ophthalmology Times*, Aug. 15, 1988, p. 27.

Jaffe, Norman, et al., "Preoperative Estimation of Intraocular Implant Lens Power," *Pseudophakos*, C.V. Mosby Company, St. Louis, 1978, pp. 58-60.

Bohn, Virginia, "Biofocal IOL Implanted in England; U.S. Trials May Begin This Month," *Ocular Surgery News*, vol. 5, No. 11, Jun. 1, 1987, pp. 1, 12-13.

Bohn, Virginia, "No Near Corrections Needed by Almost 50 in Biofocal IOL Series," *Ocular Surgery News*, vol. 5, No. 11, Jun. 1, 1987, pp. 1, 14-15.

"The 3M Multifocal IOL," *3m Health Care Brochure*, 1988, pp. 1-4.

The Shah Bifocal Universal MK II Intraocular Lens.

"Electrical Conduction in Gases," *McGraw-Hill Encyclopedia of Science & Technology*, p. 78, 1987.

"Corona Discharge," *McGraw-Hill Encyclopedia of Science & Technology*, p. 437, 1987.

"Glow Discharge," *McGraw-Hill Encyclopedia of Science & Technology*, p. 137, 1987.

"Arc Discharge," *McGraw-Hill Encyclopedia of Science & Technology*, p. 11, 1987.

Donald, Tim, "Silicone Demonstrates Suitable Optic Characteristics in Resolution Testing," *Ocular Surgery News*, vol. 6, No. 16, Aug. 15, 1988, pp. 16-17.

"Resolution Efficiency in Water Supported as New IOL Standard," *Ophthalmology Times*, Apr. 15, 1987, pp. 46 and 48.

Primary Examiner—Mathieu D. Vargot

Attorney, Agent, or Firm—Knobbe, Martens Olson & Bear, LLP

[57] ABSTRACT

A lens, having an optical power surface, which may have multiple radii portions or aspherical portions as well as spherical portions, is molded in a coined mold. A pair of core pins, positioned within the mold cavity during the lens forming process, will produce a pair of haptic-mounting holes within the lens. As the lenses are subsequently tumbled to remove flash, indentations will form adjacent to the haptic-mounting holes. These indentations allow for tangential attachment of the haptic to the lens which, in turn, enables maximum flexibility without exceeding the width of the optic.

3 Claims, 6 Drawing Sheets

