



US009408936B2

(12) **United States Patent**  
**Esses**

(10) **Patent No.:** **US 9,408,936 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

- (54) **AIR FRESHENER**
- (71) Applicant: **Alfred Esses**, Brooklyn, NY (US)
- (72) Inventor: **Alfred Esses**, Brooklyn, NY (US)
- (73) Assignee: **Alfred Esses**, Brooklyn, NY (US)

7,687,037	B2	3/2010	Wheatley et al.
7,687,038	B2	3/2010	Wheatley et al.
8,480,960	B2	7/2013	Wheatley et al.
8,662,480	B1	3/2014	Irvin
8,673,223	B1	3/2014	Finlay
2014/0112649	A1	4/2014	Irvin et al.
2014/0158789	A1	6/2014	Haymond
2014/0161672	A1	6/2014	Wheatley et al.

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 39 days.

**FOREIGN PATENT DOCUMENTS**

CN	200947724	Y	9/2007
CN	202950996	U	5/2013
GB	2292271	A	2/1996

\* cited by examiner

- (21) Appl. No.: **14/341,382**
- (22) Filed: **Jul. 25, 2014**

- (65) **Prior Publication Data**  
US 2016/0022855 A1 Jan. 28, 2016

*Primary Examiner* — Monzer R Chorbaji  
(74) *Attorney, Agent, or Firm* — Moritt Hock & Hamroff LLP; Steven S. Rubin, Esq.

- (51) **Int. Cl.**  
**A61L 9/00** (2006.01)  
**A62B 7/08** (2006.01)  
**A01G 13/06** (2006.01)  
**A61L 9/03** (2006.01)  
**B60H 3/00** (2006.01)

(57) **ABSTRACT**

Technologies are generally described for air freshener devices. The devices may comprise an insertion section including electrodes. The electrodes may be effective to receive and conduct an electric current and to secure the devices to an electric source. The devices may include a base. The base may be attached the insertion section. The base may include a port effective to receive at least part of the electric current from the electrodes. The base may include a collar effective to apply heat sufficient to release a fragrance from a material infused with the fragrance when at least part of the electrical current is supplied to the collar from the electrodes. The device may include a cap. The cap may have a ring shaped cross-section and may be sized and shaped so as to be connectable to the base such that the port is accessible when the cap is connected.

- (52) **U.S. Cl.**  
CPC ..... **A61L 9/03** (2013.01); **B60H 3/0007** (2013.01)

- (58) **Field of Classification Search**  
CPC ..... A61L 9/00; A61L 9/03; A61L 9/037  
USPC ..... 422/1, 5, 123, 125, 306; 392/386, 391, 392/394  
See application file for complete search history.

- (56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
3,872,280 A \* 3/1975 Van Dalen ..... A61L 9/03  
128/203.27  
6,099,137 A 8/2000 McCormack

**20 Claims, 3 Drawing Sheets**

