



US009409438B2

(12) **United States Patent**  
**Ohtsuka**

(10) **Patent No.:** **US 9,409,438 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **WRITING INSTRUMENT WITH ERASING MEMBER**

(2013.01); **B43K 7/00** (2013.01); **B43K 7/005** (2013.01); **B43K 7/02** (2013.01); **B43K 23/02** (2013.01); **B43K 23/124** (2013.01); **B43K 23/126** (2013.01); **B43K 25/022** (2013.01); **B43K 25/026** (2013.01); **B43K 29/02** (2013.01); **B43L 19/0025** (2013.01); **B43L 19/0075** (2013.01); **B43L 19/0087** (2013.01)

(71) Applicant: **MITSUBISHI PENCIL COMPANY, LIMITED**, Tokyo (JP)

(72) Inventor: **Hiroshi Ohtsuka**, Yokohama (JP)

(73) Assignee: **Mitsubishi Pencil Company, Limited**, Tokyo (JP)

(58) **Field of Classification Search**  
CPC ..... B43K 3/00; B43K 29/02; B43K 23/124; B43K 23/126; B43L 19/0075  
See application file for complete search history.

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 118 days.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,224,992 A \* 5/1917 Ziemer ..... B43K 29/02 15/427  
1,847,163 A \* 3/1932 Hehl ..... B43K 3/00 15/444

(Continued)

FOREIGN PATENT DOCUMENTS

JP 60-138774 U 9/1985  
JP 06-075780 U 10/1994

(Continued)

*Primary Examiner* — Randall Chin

(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(21) Appl. No.: **14/362,790**

(22) PCT Filed: **Dec. 4, 2012**

(86) PCT No.: **PCT/JP2012/081392**

§ 371 (c)(1),  
(2) Date: **Jun. 4, 2014**

(87) PCT Pub. No.: **WO2013/084894**

PCT Pub. Date: **Jun. 13, 2013**

(65) **Prior Publication Data**

US 2014/0331448 A1 Nov. 13, 2014

(30) **Foreign Application Priority Data**

Dec. 9, 2011 (JP) ..... 2011-270080  
May 30, 2012 (JP) ..... 2012-123324

(51) **Int. Cl.**

**B43K 3/00** (2006.01)  
**B43K 23/12** (2006.01)  
**B43L 19/00** (2006.01)  
**B43K 29/02** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **B43L 19/0068** (2013.01); **B43K 3/00**

(57) **ABSTRACT**

A writing instrument (1) is provided with an erasing member (2) mounted to the rear end section of the writing instrument body (3) or to the front end section of a cap (4). The end section has a fitting section (14) which is disposed on the center axis and a connection section (15) which connects the end section and the fitting section (14). The erasing member (2) has a fitting hole (2c) which receives both the fitting section (14) and the connection section (15). When the erasing member (2) is mounted in position, a gap space (17) is formed around the connection section (15).

**4 Claims, 16 Drawing Sheets**

