

invention may also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. However, some, if not all aspects of the invention can be practiced on stand-alone computers. In a distributed computing environment, program modules may be located in both local and remote memory storage devices.

With reference to FIG. 17, an exemplary system for implementing the various aspects of the invention includes a computer 720, including a processing unit 721, a system memory 722, and a system bus 723 that couples various system components including the system memory to the processing unit 721. The processing unit 721 may be any of various commercially available processors. It is to be appreciated that dual microprocessors and other multi-processor architectures also may be employed as the processing unit 721.

The system bus may be any of several types of bus structure including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of commercially available bus architectures. The system memory may include read only memory (ROM) 724 and random access memory (RAM) 725. A basic input/output system (BIOS), containing the basic routines that help to transfer information between elements within the computer 720, such as during start-up, is stored in ROM 724.

The computer 720 further includes a hard disk drive 727, a magnetic disk drive 728, e.g., to read from or write to a removable disk 729, and an optical disk drive 730, e.g., for reading from or writing to a CD-ROM disk 731 or to read from or write to other optical media. The hard disk drive 727, magnetic disk drive 728, and optical disk drive 730 are connected to the system bus 723 by a hard disk drive interface 732, a magnetic disk drive interface 733, and an optical drive interface 734, respectively. The drives and their associated computer-readable media provide nonvolatile storage of data, data structures, computer-executable instructions, etc. for the computer 720. Although the description of computer-readable media above refers to a hard disk, a removable magnetic disk and a CD, it should be appreciated by those skilled in the art that other types of media which are readable by a computer, such as magnetic cassettes, flash memory cards, digital video disks, Bernoulli cartridges, and the like, may also be used in the exemplary operating environment, and further that any such media may contain computer-executable instructions for performing the methods of the present invention.

A number of program modules may be stored in the drives and RAM 725, including an operating system 735, one or more application programs 736, other program modules 737, and program data 738. It is noted that the operating system 735 in the illustrated computer may be substantially any suitable operating system.

A user may enter commands and information into the computer 720 through a keyboard 740 and a pointing device, such as a mouse 742. Other input devices (not shown) may include a microphone, a joystick, a game pad, a satellite dish, a scanner, or the like. These and other input devices are often connected to the processing unit 721 through a serial port interface 746 that is coupled to the system bus, but may be connected by other interfaces, such as a parallel port, a game port or a universal serial bus (USB). A monitor 747 or other type of display device is also connected to the system bus 723 via an interface, such as a video adapter 748. In addition to the monitor, computers typically include other peripheral output devices (not shown), such as speakers and printers.

The computer 720 may operate in a networked environment using logical connections to one or more remote computers, such as a remote computer 749. The remote computer 749 may be a workstation, a server computer, a router, a peer device or other common network node, and typically includes many or all of the elements described relative to the computer 720, although only a memory storage device 750 is illustrated in FIG. 17. The logical connections depicted in FIG. 17 may include a local area network (LAN) 751 and a wide area network (WAN) 752. Such networking environments are commonplace in offices, enterprise-wide computer networks, Intranets and the Internet.

When employed in a LAN networking environment, the computer 720 may be connected to the local network 751 through a network interface or adapter 753. When utilized in a WAN networking environment, the computer 720 generally may include a modem 754, and/or is connected to a communications server on the LAN, and/or has other means for establishing communications over the wide area network 752, such as the Internet. The modem 754, which may be internal or external, may be connected to the system bus 723 via the serial port interface 746. In a networked environment, program modules depicted relative to the computer 720, or portions thereof, may be stored in the remote memory storage device. It will be appreciated that the network connections shown are exemplary and other means of establishing a communications link between the computers may be employed.

In accordance with the practices of persons skilled in the art of computer programming, the present invention has been described with reference to acts and symbolic representations of operations that are performed by a computer, such as the computer 720, unless otherwise indicated. Such acts and operations are sometimes referred to as being computer-executed. It will be appreciated that the acts and symbolically represented operations include the manipulation by the processing unit 721 of electrical signals representing data bits which causes a resulting transformation or reduction of the electrical signal representation, and the maintenance of data bits at memory locations in the memory system (including the system memory 722, hard drive 727, floppy disks 729, and CD-ROM 731) to thereby reconfigure or otherwise alter the computer system's operation, as well as other processing of signals. The memory locations wherein such data bits are maintained are physical locations that have particular electrical, magnetic, or optical properties corresponding to the data bits.

What has been described above are preferred aspects of the present invention. It is, of course, not possible to describe every conceivable combination of components or methodologies for purposes of describing the present invention, but one of ordinary skill in the art will recognize that many further combinations and permutations of the present invention are possible. Accordingly, the present invention is intended to embrace all such alterations and variations that fall within the spirit and scope of the appended claims.

What is claimed is:

1. A system that facilitates the administration of an application, comprising:
 - a resource identifier that identifies resources associated with the application;
 - a manifest that logs the resources; and
 - an aggregator that aggregates a subset of the resources into one or more application images to facilitate administration of the application.