



US009409442B2

(12) **United States Patent**  
**Nollenberger**

(10) **Patent No.:** **US 9,409,442 B2**

(45) **Date of Patent:** **Aug. 9, 2016**

(54) **AXIAL SECURING RING, BEARING ARRANGEMENT AND PRODUCTION METHOD THEREFOR**

(58) **Field of Classification Search**

CPC ... B60B 27/0078; F16H 57/021; F16C 19/54; F16C 35/067; F16C 35/07; F16C 35/077; F16C 35/073; F16C 2361/61; F16C 19/06; F16C 2226/74; F16C 33/586

See application file for complete search history.

(71) Applicant: **GETRAG Getriebe-und Zahnradfabrik Hermann Hagenmeyer GmbH & Cie KG**, Untergruppenbach (DE)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,989,750 A 2/1935 Garrett  
2,051,704 A 8/1936 Harris

(Continued)

FOREIGN PATENT DOCUMENTS

DE 19 69 834 U 10/1967  
DE 19730749 A1 1/1998

(Continued)

OTHER PUBLICATIONS

Partial European Search Report for Application No. EP 20150153111, dated Jul. 24, 2015, in 9 pages.

(Continued)

(72) Inventor: **Frank Nollenberger**, Besigheim (DE)

(73) Assignee: **GETRAG GETRIEBE-UND ZAHNRADFABRIK HERMANN HAGENMEYER GMBH & CIE KG**, Untergruppenbach (DE)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/620,128**

(22) Filed: **Feb. 11, 2015**

(65) **Prior Publication Data**

US 2015/0224821 A1 Aug. 13, 2015

(30) **Foreign Application Priority Data**

Feb. 11, 2014 (DE) ..... 10 2014 101 645

(51) **Int. Cl.**

**F16C 43/00** (2006.01)  
**B60B 27/00** (2006.01)  
**F16C 35/073** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **B60B 27/0078** (2013.01); **F16C 19/54** (2013.01); **F16C 35/067** (2013.01); **F16C 35/073** (2013.01); **F16C 19/06** (2013.01); **F16C 2226/74** (2013.01); **F16C 2361/61** (2013.01); **F16H 57/023** (2013.01)

*Primary Examiner* — Adam D Rogers

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP

(57) **ABSTRACT**

A bearing arrangement is provided having an axial securing ring that inserts into a bearing-seat radial groove of a bearing carrier to secure an anti-friction bearing axially in relation to the bearing carrier. The axial securing ring is an open flat ring with an annular section. Radially projecting lugs are provided at each end of the annular section. The radial width of the annular section is substantially constant over the circumference of the annular section. The lugs are produced by bending the axial securing ring with respect to the annular section. The axial securing ring is plane-ground on its axial sides.

**7 Claims, 3 Drawing Sheets**

