



(12) **United States Patent**
Ikeya et al.

(10) **Patent No.:** **US 9,411,043 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **RADAR APPARATUS AND
COMPUTER-READABLE STORAGE
MEDIUM**

(71) Applicant: **FUJITSU LIMITED**, Kawasaki-shi,
Kanagawa (JP)

(72) Inventors: **Tomonori Ikeya**, Sagamihara (JP);
Junko Kajiki, Kawasaki (JP); **Kazuhiko
Shite**, Sagamihara (JP); **Mitsuru Ochi**,
Kawasaki (JP)

(73) Assignee: **FUJITSU LIMITED**, Kawasaki (JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 364 days.

(21) Appl. No.: **14/090,631**

(22) Filed: **Nov. 26, 2013**

(65) **Prior Publication Data**

US 2014/0266855 A1 Sep. 18, 2014

(30) **Foreign Application Priority Data**

Mar. 18, 2013 (JP) 2013-055484

(51) **Int. Cl.**
G01S 13/93 (2006.01)
G01S 7/35 (2006.01)
G01S 13/34 (2006.01)

(52) **U.S. Cl.**
CPC **G01S 13/931** (2013.01); **G01S 7/354**
(2013.01); **G01S 13/345** (2013.01)

(58) **Field of Classification Search**
CPC G01S 7/354; G01S 13/931; G01S 13/345
USPC 342/27, 70-72, 115, 175, 190, 195
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,075,686 A * 2/1978 Calle G06F 12/0888
711/113
4,080,599 A * 3/1978 Conti G01S 7/2923
342/195
4,298,929 A * 11/1981 Capozzi G06F 12/0804
711/118
4,357,656 A * 11/1982 Saltz G11C 29/24
711/113

(Continued)

FOREIGN PATENT DOCUMENTS

EP 2034331 A1 3/2009
JP 2001-223660 8/2001

(Continued)

OTHER PUBLICATIONS

Korean Office Action mailed Oct. 31, 2014 in corresponding Korean
Patent Application No. 10-2013-151301.

(Continued)

Primary Examiner — Peter Bythrow

(74) *Attorney, Agent, or Firm* — Staas & Halsey LLP

(57) **ABSTRACT**

A radar apparatus to detect an object includes a detecting unit
configured to detect the object based on a reflected wave
received in response to transmitting a transmission wave, in
order to output a detection result of the object, a storage unit
including a first storage part to store the detection result, and
a second storage part to store a copy of information stored in
the first storage part based on a copy command, and a select-
ing unit configured to select one of the first storage part and
the second storage part as an access destination, in order to
output the detection result stored in one of the first storage
part and the second storage part selected as the access desti-
nation.

11 Claims, 15 Drawing Sheets

1

