



US009408344B1

(12) **United States Patent**
Langenfeld

(10) **Patent No.:** **US 9,408,344 B1**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **THREE WHEELED VEHICLE**

(56) **References Cited**

(71) Applicant: **Hydro-Gear Limited Partnership**,
Sullivan, IL (US)

U.S. PATENT DOCUMENTS

(72) Inventor: **Thomas J. Langenfeld**, Sullivan, IL
(US)

665,270 A	1/1901	Rumely	
810,881 A	1/1906	Pfouts et al.	
849,145 A	4/1907	Ledwinka	
2,620,612 A *	12/1952	De Eugenio	A01D 34/64 180/210
2,891,370 A *	6/1959	Musgrave	A01D 34/64 180/21
3,780,504 A	12/1973	Haseloff	
4,024,695 A	5/1977	Haseloff	
4,335,567 A *	6/1982	Comer	A01D 43/063 56/12.7
4,914,894 A *	4/1990	Geiger	A01D 34/63 180/19.1

(73) Assignee: **Hydro-Gear Limited Partnership**,
Sullivan, IL (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/535,664**

(Continued)

(22) Filed: **Nov. 7, 2014**

FOREIGN PATENT DOCUMENTS

Related U.S. Application Data

EP	1180468 A1	2/2002
WO	2012091699 A1	7/2012

(60) Provisional application No. 61/902,108, filed on Nov.
8, 2013, provisional application No. 61/919,423, filed
on Dec. 20, 2013.

OTHER PUBLICATIONS

U.S. Appl. No. 14/577,441, filed Dec. 19, 2014.

(51) **Int. Cl.**

<i>A01D 34/66</i>	(2006.01)
<i>A01D 34/81</i>	(2006.01)
<i>A01B 69/00</i>	(2006.01)
<i>A01D 43/063</i>	(2006.01)

Primary Examiner — John G Weiss

(74) *Attorney, Agent, or Firm* — Neal, Gerber & Eisenberg
LLP

(52) **U.S. Cl.**

CPC *A01D 34/66* (2013.01); *A01B 69/007*
(2013.01); *A01D 34/667* (2013.01); *A01D*
34/81 (2013.01); *A01D 43/063* (2013.01)

(57) **ABSTRACT**

A three-wheeled mowing vehicle is disclosed. The vehicle
has a frame and a prime mover. Two steered wheels, steered
by a steering mechanism, are near the front of the vehicle and
a single non-steered wheel is near the rear of the vehicle. The
vehicle has a deck that houses rotatable cutting blades. Por-
tions of the deck are positioned in front of and adjacent each
side of the rear wheel. A first rotatable cutting blade is posi-
tioned adjacent a first side of the rear wheel and a second
rotatable cutting blade is positioned adjacent the opposite
side of the rear wheel. One or more additional cutting blades
are positioned in front of the rear wheel.

(58) **Field of Classification Search**

CPC A01D 34/00; A01D 2034/6831; A01D
34/863; A01B 69/007
USPC 56/11.9, 17.5, 157, 200, 253, 14.7, 202,
56/203; 180/210, 211, 212

See application file for complete search history.

20 Claims, 5 Drawing Sheets

