



US009408345B2

(12) **United States Patent**
Matsugi et al.

(10) **Patent No.:** **US 9,408,345 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **WORK VEHICLES**
(71) Applicant: **ISEKI & CO., LTD.**, Ehime-ken (JP)
(72) Inventors: **Satoshi Matsugi**, Ehime-ken (JP);
Hiroataka Toda, Ehime-ken (JP)
(73) Assignee: **ISEKI & CO., LTD.**, Ehime-Ken (JP)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 96 days.

6,138,444 A * 10/2000 Torras, Sr. A01D 34/64
56/14.7
2004/0000130 A1* 1/2004 Bartel A01D 34/69
56/11.3
2006/0070366 A1* 4/2006 Laskowski A01D 34/74
56/14.9
2006/0090442 A1* 5/2006 Komiya A01D 34/64
56/14.7
2006/0174601 A1* 8/2006 Piontek A01D 34/64
56/11.3
2008/0034723 A1* 2/2008 Wright A01D 34/74
56/17.1
2008/0184687 A1* 8/2008 Scherbring A01D 34/64
56/10.1
2008/0190084 A1* 8/2008 Piontek A01D 34/64
56/11.3

(21) Appl. No.: **14/316,725**

(22) Filed: **Jun. 26, 2014**

(65) **Prior Publication Data**
US 2015/0000238 A1 Jan. 1, 2015

(30) **Foreign Application Priority Data**
Jun. 27, 2013 (JP) 2013-134417

(51) **Int. Cl.**
A01D 34/66 (2006.01)
(52) **U.S. Cl.**
CPC **A01D 34/661** (2013.01)
(58) **Field of Classification Search**
CPC A01D 34/54; A01D 34/64; A01D 34/66;
A01D 34/74; A01D 67/04; A01D 67/00;
A01D 67/005; A01D 34/661
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS
5,865,020 A * 2/1999 Busboom A01D 34/74
56/10.8
5,946,894 A * 9/1999 Eavenson A01D 34/64
56/15.4

FOREIGN PATENT DOCUMENTS

JP 2012070696 4/2012
* cited by examiner

Primary Examiner — Robert Pezzuto
Assistant Examiner — Adam Behrens
(74) *Attorney, Agent, or Firm* — Finnegan, Henderson, Farabow, Garrett & Dunner LLP

(57) **ABSTRACT**

In a work vehicle, because of growing need to equip a DPF for exhaust gas countermeasures near an engine and a request of increasing the size of a fuel tank, a system including the fuel tanks provided below a floor step and on left and right sides of a transmission case has been employed. However, when a lawn mower is installed between front wheels and rear wheels, an increasing width of a vehicle body becomes a problem.

To solve the problem, a locus of the raising and lowering operation of a lawn mower **5** is specified by a parallel link formed of left and right front links **43, 43** and left and right mid links **45, 45**, and in a work vehicle where the lawn mower **5** is freely raised and lowered, the left and right mid links **45, 45** are respectively disposed between a transmission case **3** and fuel tanks **16L, 16L**.

2 Claims, 11 Drawing Sheets

